

HUMIDITY & TEMPERATURE METER

H 991-T-A

Measurement range	Temperature	-10°C ~ +50°C (14°F ~ 122°F)
	Humidity	5%RH ~ 98%RH
Accuracy	Temperature	±1°C (±1.8°F)
	Humidity	±3%RH (in 25°C, 30~99%RH) ±5%RH (in 25°C, 10~30%RH)
Resolution	Temperature	0.1°C / 0.1 °F
	Humidity	0.1%RH
Sampling time	2.5 times/sec	
Operation conditions	Temperature	0°C ~ 50°C (32°F ~ 122°F)
	Humidity	< 98%RH
Power supply	9V battery	
Storage condition	Temperature	-10°C ~ 60°C (14°F ~ 140°F)
	Humidity	0%RH ~ 90%

- * °C/°F selection
- * Auto / Manual power shut off
- * Low battery indication
- * Data hold
- * Sampling rate: 2.5 times/sec
- * Max/ Min function
- * Large LCD temperature & humidity dual display
- * Unit size: 207*70*30mm



H 99-T-B



- * °C/°F selection
- * Auto / Manual power shut off
- * Low battery indication
- * Data hold
- * Sampling rate: 2.5 times/sec
- * Max/ Min function
- * Large LCD temperature & humidity dual display
- * Unit size: 207*70*30mm

humidity	range: 0%~100%RH		
	range	resolution	precision
	0%~20%RH	0.1	4.5%
	20%~80%RH		3.0%
80%~100%RH		4.5%	
temperature	range: -30°C ~ 70°C		
	range	resolution	precision
	-30°C ~ 0°C	0.1°C / 0.2°F	1.0°C
	0°C ~ 70°C		0.5°C
	-22°F ~ 32°F		1.8°F
	32°F ~ 158°F		0.9°F
sizes: 152*35.5*52.5mm			
weight: 92.7g			

H 992-TK

Temperature range	-10°C~50°C (-30°C~1000°C K-type)
Accuracy of temperature	±1°C or ±1.8 F (±3%or±2°C K-type)
Humidity range	10%RH~98%RH
Accuracy of humidity	±3%(in the 25°C, 30 - 95%RH) ±5%(in the 25°C, 10 - 30%RH)
Temperature resolution	0.1°C/0.1°F
Humidity resolution	0.1%RH
Sampling rate	2.5times/sec
Operating conditions	0°C - 50°C (32°F- 122°F) ≤80%RHnon-condensing
Power	9V battery
Storage conditions	-10°C - 60°C (14°F- 140°F) 0%RH-90%RH

- °C/°F selection
- Auto/Manual power shut off
- Low battery indication
- Data hold
- Max/Min function
- K-type thermocouple temperature measuring
- Large LCD temperature & humidity dual display



H 993-T



Temperature range	-10°C~50°C
Accuracy of temperature	±1°C or ±1.8F
Humidity range	5%RH~99%RH
Accuracy of humidity	±3% RH (30%RH ~ 90%RH) ±5% RH (10%RH ~ 30%RH)
Temperature resolution	0.1°C
Humidity resolution	0.1%RH
Sampling rate	2 times/sec
Power	AA*4 battery (Alkaline or DC Adapter)

- °C/°F selection
- Auto power off
- Data hold
- Max/Min function
- Large LCD temperature & humidity dual display
- Size: 221*78*35 mm
- Product net weight: 194g