




USB HAND HELD THERMO-HYGROMETER

NEW



RH calibration solution
33% - 99033S (Green)
75% - 99075S (Blue)



Features

- Compact size with structure NEW UTILITY patent
- Measure Temperature and Relative humidity, model 98873 monitor Wet bulb global temperature and Heat index for heat stroke prevention
- Self-calibration by salt bottle with 33% low humidity and 75% high humidity solution. Salt bottles and USB software with CD are optional package
- Hold function for holding readings on display
- Large dual display with battery low indication
- Quick response. High accuracy
- Big LCD display with high resolution
- Enable Auto power off and disable function
- Warranty in 2 years from purchasing

Standard Accessories

- Meter, Battery, Operation manual and carrying case

Applications

- HVAC & Home inspection for examining the heating and air conditioning systems.
- Construction & Industrial inspection
- Outdoors weather monitoring avoid unnecessary heat stroke while training outside



Specifications

	98871	98873	98875
Temp.range	-20~50C (-4~122F)		
Accuracy	+/-0.6C		
RH % range	0.1~99.9%		
Accuracy	+/-3% (10-90%), others +/-5%		
Heat Index (HI)	N/A	N/A	YES
Wet Bulb Global Temp.(WBGT)	N/A	N/A	YES
Dew Point Temp.(DP)	N/A	YES	YES
Wet Bulb Temp. (WB)	N/A	YES	YES
HI/LO alarm	N/A	YES	YES
Self-calibration	N/A	YES	YES
Maximum/ Minimum/Recall	YES		
Reset	YES		
Memory	N/A	99 point	99 point
Average	YES		
Power	AAA x 3 pcs		
USB Interface	N/A	YES	YES
Operating Temp.RH	0~50C(32~122°F) , <80%RH		
Meter size	160*60*40mm (Meter) , Sensor tip(31mm)		