


Technical Information

Liquiphant M

FTL50, FTL51, FTL50H, FTL51H

Vibronic

Point level switch for all kinds of liquids



Application

- Process temperatures from $-50\text{ }^{\circ}\text{C}$ to $150\text{ }^{\circ}\text{C}$ (-58 to $302\text{ }^{\circ}\text{F}$)
- Pressures up to 100 bar (1450 psi)
- Viscosities up to $10,000\text{ mm}^2/\text{s}$ (cSt)
- For liquids with densities $\geq 0.5\text{ g/cm}^3$ (SGU)

FTL50: Compact design

FTL51: Extension pipe up to 3 m (9.8 ft) and up to 6 m (20 ft) on request

FTL50H, FTL51H: Certified for the food and pharmaceutical industries

Ideal substitute for float switches, as reliable function not affected by flow, turbulence, bubbles, foam, vibration, solids content or buildup.

Your benefits

- Recommended for safety systems requiring functional safety to SIL2/SIL3 as per IEC 61508/IEC 61511-1
- Design in accordance with ASME B31.3
- Recommended for use in sterile applications in the life science industry (design in accordance with ASME BPE)
- No adjustment: quick, low-cost startup
- No mechanically moving parts: no maintenance, no wear, long operating life
- Functional safety: Monitoring of tuning fork for damage
- Compact stainless steel housing (optional): the IP69K protection rating guarantees that the unit remains impermeable, even in the event of intensive cleaning or flooding for several hours.

Table of contents


Application	4	Connectable load	14
Point level detection	4		
Function and system design	4	Electronic insert FEL56 (NAMUR L-H edge)	15
Measuring principle	4	Power supply	15
Modularity	4	Electrical connection	15
Electronic versions	5	Output signal	15
Electronics for continuous density measurement	5	Signal on alarm	15
Galvanic isolation	5	Connectable load	15
Design	5		
Input	5	Electronic insert FEL58 (NAMUR H-L edge)	16
Measured variable	5	Power supply	16
Measuring range (detection range)	5	Electrical connection	16
Density	5	Output signal	16
		Signal on alarm	16
		Connectable load	16
Electronic insert FEL51 (AC 2-wire)	6	Electronics FEL58 (NAMUR H-L edge, in compact housing)	17
Power supply	6	Power supply	17
Electrical connection	6	Electrical connection	17
Output signal	6	Output signal	17
Signal on alarm	6	Signal on alarm	17
Connectable load	6	Connectable load	17
Electronics FEL51 (AC, in compact housing)	8	Electronic insert FEL57 (PFM)	18
Power supply	8	Power supply	18
Electrical connection	8	Electrical connection	18
Output signal	8	Output signal	19
Signal on alarm	8	Signal on alarm	19
Connectable load	8	Connectable load	19
Electronic insert FEL52 (DC PNP)	10	Electronic insert FEL50A (PROFIBUS PA)	20
Power supply	10	Power supply	20
Electrical connection	10	Electrical connection	20
Output signal	10	Output signal	21
Signal on alarm	10	Signal on alarm	21
Connectable load	10		
Electronics FEL52 (DC PNP, in compact housing) ..	11	Electronic insert FEL50D (density)	22
Power supply	11	Power supply	22
Electrical connection	11	Electrical connection	22
Output signal	11	Signal on alarm	22
Signal on alarm	12	Adjustment	22
Connectable load	12	Operating principle	23
		Light signals	23
Electronic insert FEL54 (AC/DC with relay output) ..	13	Connection and function	24
Power supply	13	Connecting cables	24
Electrical connection	13	Safety mode	24
Output signal	13	Switching time	24
Signal on alarm	13	Switch-on behavior	24
Connectable load	13		
Electronic insert FEL55 (8/16 mA)	14	Performance characteristics	24
Power supply	14	Reference operating conditions	24
Electrical connection	14	Maximum measured error	24
Output signal	14	Repeatability	24
Signal on alarm	14	Hysteresis	24

Influence of medium temperature	24	Weather protection cover	52
Influence of medium density	24	Lap joint flange	52
Influence of medium pressure	24	Lap joint flanges	53
Operating conditions.....	25	Sliding sleeves for unpressurized operation	53
Installation	25	High pressure sliding sleeves	54
Examples of mounting	25	Cover with sight glass	55
Orientation	27	Cover with sight glass	55
Environment.....	27	Circular connector	55
Ambient temperature range	27	Documentation.....	56
Storage temperature	27	Operating Instructions	56
Installation height as per		Technical Information	57
IEC61010-1 Ed.3	27	Functional safety (SIL)	57
Climate class	27	Safety Instructions (ATEX)	58
Degree of protection	28	Safety Instructions (NEPSI)	58
Vibration resistance	28	Control Drawings	58
Electromagnetic compatibility	28	System information	58
Medium conditions	29		
Medium temperature	29		
Thermal shock	29		
Medium pressure pe	29		
Test pressure	29		
State of aggregation	29		
Density	29		
Viscosity	29		
Solids content	29		
Lateral loading capacity	29		
Mechanical construction	30		
Design	30		
Dimensions	31		
Weights	36		
Materials and surfaces	36		
Process connections	37		
Human interface	38		
Electronic inserts	38		
Compact housing	39		
Operating concept	41		
Certificates and approvals	41		
CE mark	41		
C-tick mark	41		
General approvals	41		
CRN approval	42		
Process seal according to ANSI/ISA 12.27.01	42		
Other certificates	42		
Manufacturer declarations	42		
Use in hazardous zones	42		
ASME B 31.3	43		
Pressure equipment directive	43		
Ordering information	43		
Liquiphant M FTL50, FTL51 product structure	43		
Liquiphant M FTL50H, FTL51H product structure	47		
Accessories	50		
Weld-in adapter	50		

Application

Point level detection

Maximum or minimum detection in tanks or pipes containing all kinds of liquids, including use in hazardous areas, food and pharmaceuticals.



L00-FTL5xxxx-11-05-xx-xx-000

Function and system design


Measuring principle

The sensor's fork vibrates at its intrinsic frequency. This frequency is reduced when covered with liquid. This change in frequency causes the point level switch to switch.

Modularity

Point level switch


Liquiphant M FTL with electronic versions
FEL51, FEL52, FEL54



L00-FTL5xxxx-15-05-xx-xx-000

Point level switch

Liquiphant M FTL with electronic versions
FEL55, FEL56, FEL57, FEL58
for connecting to a separate switching unit
or an isolating amplifier FEL50A
for connecting to a PROFIBUS PA segment



L00-FTL5xxxx-15-05-xx-en-000

Electronic versions	<p>FEL51: Two-wire AC version; Switches the load directly into the power supply circuit via an electronic switch.</p> <p>FEL52: Three-wire DC version; Switches the load via the transistor (PNP) and separate connection e.g. in conjunction with programmable logic controllers (PLCs), DI modules as per EN 61131-2.</p> <p>FEL54: Universal current version with relay output; Switches the loads via 2 floating change-over contacts.</p> <p>FEL55: Signal transmission 16/8 mA on two-wire cabling e.g. in conjunction with programmable logic controllers (PLCs), AI modules 4 to 20 mA as per EN 61131-2.</p> <p>FEL56: For separate switching unit; signal transmission L-H edge 0.6 to 1.0 / 2.2 to 2.8 mA to EN 50227 (NAMUR) on two-wire cabling.</p> <p>FEL58: For separate switching unit; signal transmission H-L edge 2.2 to 3.5 / 0.6 to 1.0 mA to EN 50227 (NAMUR) on two-wire cabling. Checking of connecting cabling and other devices by pressing a key on the electronic insert.</p> <p>FEL57: For separate switching unit; PFM signal transmission; Current pulses superposed on the power supply along the two-wire cabling. Proof test from the switching unit without changing levels.</p> <p>FEL50A: For connecting to PROFIBUS PA; Cyclic and acyclic data exchange acc. to PROFIBUS-PA Profile 3.0 Discrete Input</p>
----------------------------	--

Electronics for continuous density measurement	<p>FEL50D: For connecting to Density Computer FML621</p>
---	--

Galvanic isolation	<p>FEL51, FEL52, FEL50A: between sensor and power supply</p> <p>FEL54: between sensor and power supply and load</p> <p>FEL55, FEL56, FEL57, FEL58, FEL50D: see connected switching unit</p>
---------------------------	---

Design	<p>FTL50: Compact</p> <p>FTL51: With extension pipe</p> <p>FTL50H: Compact, with polished tuning fork and hygienic process connections</p> <p>FTL51H: With extension pipe, polished tuning fork and hygienic process connections</p>
---------------	--

Input

Measured variable	Level (limit value)
Measuring range (detection range)	<p>FTL50: dependent on mounting point</p> <p>FTL51: dependent on mounting point and the extension pipe ordered. Standard extension pipe up to 3 m (9.8 ft) and up to 6 m (20 ft) on request.</p>
Density	Setting on the electronic insert > 0.5 g/cm ³ (SGU) or > 0.7 g/cm ³ (SGU) (others on request)

Electronic insert FEL51 (AC 2-wire)

Power supply

Supply voltage: AC 19 to 253 V
 Power consumption: < 0.83 W
 Residual current consumption: < 3.8 mA
 Short-circuit protection
 Overvoltage protection FEL51: overvoltage category III

Electrical connection


Two-wire AC connection

Switches the load directly into the power supply circuit via an electronic switch.

Always connect in series with a load!

Check the following:

- The residual current in blocked state (up to 3.8 mA)
- That for low voltage
 - the voltage drop across the load is such that the minimum terminal voltage at the electronic insert (19 V) when blocked is not undershot.
 - the voltage drop across the electronics when switched through is observed (up to 12 V)
- That a relay cannot de-energize with holding power below 3.8 mA.
 If this is the case, a resistor should be connected parallel to the relay. An RC module is available under the part number: 71107226
- When selecting the relay, pay attention to the holding power / rated power (see "Connectable load")



L00-FTL5xxxx-04-05-xx-xx-007

Output signal

I_L = load current (switched through)

< 3.8 mA = residual current (blocked)



= lit



= unlit

L00-FTL2xxxx-07-05-xx-xx-000

Safety mode	Level	Output signal	LEDs green	red
Max.		1 $\xrightarrow{I_L}$ 2		
		1 $\xrightarrow{< 3.8 \text{ mA}}$ 2		
Min.		1 $\xrightarrow{I_L}$ 2		
		1 $\xrightarrow{< 3.8 \text{ mA}}$ 2		

L00-FTL5xxxx-04-05-xx-xx-007

Signal on alarm

Output signal on power failure or in the event of damaged sensor: < 3.8 mA

Connectable load


- Voltage drop via FEL51 $\leq 12 \text{ V}$
- Residual current if electrical switch is blocked: $\leq 3.8 \text{ mA}$
- Load switched directly into the power supply circuit via the thyristor.
 Transient (40 ms) $\leq 1.5 \text{ A}$, $\leq 375 \text{ VA}$ at 253 V or $\leq 36 \text{ VA}$ at 24 V (not short-circuit-proof)

The load is switched via an electronic switch directly in the power circuit.

Always connect in series with a load!

Not suitable for connection to low-voltage PLC inputs!

Selection guide for relays



Minimum nominal power of load
P/S nominal power in [W] / [VA]
U operating voltage in [V]

Position	Operating voltage	Nominal power	
		min.	max.
P1 AC operation	24 V	> 1.3 VA	< 6 VA
	110 V	> 1.5 VA	< 27.5 VA
	230 V	> 2.5 VA	< 57.5 VA

Relays with less nominal power can be operated via an RC module connected in parallel (optional).

Electronics FEL51 (AC, in compact housing)

Power supply

Supply voltage: AC 19 to 253 V
 Power consumption: < 0.83 W
 Residual current consumption: < 3.8 mA
 Short-circuit protection
 Overvoltage protection FEL51: overvoltage category III

Electrical connection

Two-wire AC connection


Switches the load directly into the power supply circuit via an electronic switch.

Always connect in series with a load!

Check the following:

- The residual current in blocked state (up to 3.8 mA)
- That for low voltage

- the voltage drop across the load is such that the minimum terminal voltage at the electronic insert (19 V) when blocked is not undershot.
- the voltage drop across the electronics when switched through is observed (up to 12 V)





L00-FTL5xxxx-04-05-xx-xx-008

- That a relay cannot de-energize with holding power below 3.8 mA.













If this is the case, a resistor should be connected parallel to the relay (e.g. RC module: part number 71107226).

Output signal

I_L
 = load current (switched through)
 < 3.8 mA
 = residual current (blocked)

 = lit
 = unlit

L00-FTL2xxxx-07-05-xx-xx-000

Safety mode	Level	Output signal	LEDs green	red
Max.		1 $\xrightarrow{I_L}$ 3		
		1 $\xrightarrow{< 3.8 \text{ mA}}$ 3		
Min.		1 $\xrightarrow{I_L}$ 2		
		1 $\xrightarrow{< 3.8 \text{ mA}}$ 2		

L00-FTL5xxxx-04-05-xx-xx-0014

Signal on alarm

Output signal on power failure or in the event of damaged sensor: < 3.8 mA

Connectable load


- Voltage drop via FEL51 $\leq 12 \text{ V}$
- Residual current if electrical switch is blocked: $\leq 3.8 \text{ mA}$
- Load switched directly into the power supply circuit via the thyristor.
 Transient (40 ms) $\leq 1.5 \text{ A}$, $\leq 375 \text{ VA}$ at 253 V or $\leq 36 \text{ VA}$ at 24 V (not short-circuit-proof)

The load is switched via an electronic switch directly in the power circuit.

Always connect in series with a load!

Not suitable for connection to low-voltage PLC inputs!

Selection guide for relays



Minimum nominal power of load
 P/S nominal power in [W] / [VA]
 U operating voltage in [V]

Position	Operating voltage	Nominal power	
		min.	max.
P1 AC operation	24 V	> 1.3 VA	< 6 VA
	110 V	> 1.5 VA	< 27.5 VA
	230 V	> 2.5 VA	< 57.5 VA

Relays with less nominal power can be operated via an RC module connected in parallel (optional).

Electronic insert FEL52 (DC PNP)


Power supply

Supply voltage: DC 10 to 55 V
 Ripple: ≤ 1.7 V, 0 to 400 Hz
 Current consumption: ≤ 15 mA
 Power consumption: ≤ 0.83 W
 Reverse polarity protection
 Overvoltage protection FEL52: overvoltage category III

Electrical connection

Three-wire DC connection

Switches the load via the transistor (PNP) and separate connection.
 Preferably used with programmable logic controllers (PLC),
 DI modules as per EN 61131-2.
 Positive signal at switching output of the electronics (PNP); Output blocked on reaching point level.



L00-FTL5xxxx-04-05-xx-en-001

Output signal

I_L = load current
(switched through)

$< 100 \mu\text{A}$ = residual current
(blocked)



= lit



= unlit

L00-FTL2xxxx-07-05-xx-xx-000

Safety mode	Level	Output signal	LEDs green	red
Max.		$L+ \xrightarrow{I_L} +$ 1 ————— 3		
		$1 \xrightarrow{< 100 \mu\text{A}} 3$		
Min.		$L+ \xrightarrow{I_L} +$ 1 ————— 3		
		$1 \xrightarrow{< 100 \mu\text{A}} 3$		

L00-FTL5xxxx-04-05-xx-xx-004

Signal on alarm

Output signal on power failure or in the event of damaged sensor: $< 100 \mu\text{A}$











Connectable load

- Load switched via the transistor and separate PNP connection, \leq DC 55 V
- Load current ≤ 350 mA (pulsed overload and short-circuit protection)
- Residual current $< 100 \mu\text{A}$ (with transistor blocked).
- Capacitance load $\leq 0.5 \mu\text{F}$ at 55 V, $\leq 1.0 \mu\text{F}$ at 24 V
- Residual voltage < 3 V (with transistor switched through);

Electronics FEL52 (DC PNP, in compact housing)

Power supply	Supply voltage: DC 10 to 55 V Ripple: ≤ 1.7 V, 0 to 400 Hz Current consumption: ≤ 15 mA Power consumption: ≤ 0.83 W Reverse polarity protection Overvoltage protection FEL52: overvoltage category III
--------------	---

Electrical connection	Three-wire DC connection Preferably used with programmable logic controllers (PLC), DI module as per EN 61131-2. Positive signal at switching output of the electronics (PNP); Output blocked on reaching point level.
-----------------------	--


Connector	MAX	MIN
FTL5#(H)- #####N3# (M12x1) 52018763 		
FTL5#(H)- #####N3# (M12x1) 52010285 / 52024216 		
FTL5#(H)- #####D3# (Pg11) or FTL5#(H)- #####E3# (NPT 1/2") 		
FTL5#(H)- #####C3# 		


L00-FTL5xxxx-04-05-xx-en-010

Output signal	With valve connector or cable tail
---------------	------------------------------------













I_L = load current
(switched through)

 $< 100 \mu A$ = residual current
(blocked)

 = lit

 = unlit

L00-FTL2xxxx-07-05-
xx-xx-000

Safety mode	Level	Output signal	LEDs	
			green	red
Max.		$L+ \xrightarrow{I_L} +$ 3 → 2		
		$L+ \xrightarrow{< 100 \mu A} +$ 3 → 2		
Min.		$L+ \xrightarrow{I_L} +$ 2 → 3		
		$L+ \xrightarrow{< 100 \mu A} +$ 2 → 3		

L00-FTL5xxxx-04-05-xx-xx-004*

With M12x1 connector 52010285 / 52024216 (without LEDs)L00-FTL5xxxx-16-05-
xx-xx-002
 I_L = load current
(switched through)

 $< 100 \mu A$ = residual current
(blocked)


= lit




= unlit

L00-FTL2xxxx-07-05-
xx-xx-000

Safety mode	Level	Output signal	LEDs
Max.		$L^+ \xrightarrow{I_L} -$ 1 2	
		$L^+ < 100 \mu A \xrightarrow{-} -$ 1 2	
Min.		$L^+ \xrightarrow{I_L} -$ 1 4	
		$L^+ < 100 \mu A \xrightarrow{-} -$ 1 4	

L00-FTL5xxxx-04-05-xx-xx-010

With M12x1 connector 52018763 (with LEDs)L00-FTL5xxxx-16-05-
xx-xx-001
 I_L = load current
(switched through)

 $< 100 \mu A$ = residual current
(blocked)


= lit



= unlit

L00-FTL2xxxx-07-05-
xx-xx-000

Safety mode	Level	Output signal	LEDs
Max.		$L^+ \xrightarrow{I_L} -$ 1 2	
		$L^+ < 100 \mu A \xrightarrow{-} -$ 1 2	
Min.		$L^+ \xrightarrow{I_L} -$ 1 4	
		$L^+ < 100 \mu A \xrightarrow{-} -$ 1 4	


L00-FTL5xxxx-04-05-xx-xx-011

Signal on alarmOutput signal on power failure or in the event of damaged sensor: $< 100 \mu A$ **Connectable load**

- Load switched via the transistor and separate PNP connection, $\leq DC 55 V$
- Load current $\leq 350 mA$ (pulsed overload and short-circuit protection)
- Residual current $< 100 \mu A$ (with transistor blocked).
- Capacitance load $\leq 0.5 \mu F$ at $55 V$, $\leq 1.0 \mu F$ at $24 V$
- Residual voltage $< 3 V$ (with transistor switched through);

Electronic insert FEL54 (AC/DC with relay output)

Power supply	Supply voltage: AC 19 to 253 V, 50/60 Hz or DC 19 to 55 V Power consumption: ≤ 1.3 W Reverse polarity protection Overvoltage protection FEL54: overvoltage category III
--------------	--

Electrical connection	<p>Universal current connection with relay output</p> <p>Power supply: Please note the different voltage ranges for AC and DC.</p> <p>Output: When connecting an instrument with high inductance, provide a spark arrester to protect the relay contact. A fine-wire fuse (depending on the load connected) protects the relay contact on short-circuiting. Both relay contacts switch simultaneously.</p> <p>* When jumpered, the relay output works with NPN logic.</p> <p>** See "Connectable load"</p>  <p>L00-FTL5xxxx-04-05-xx-xx-002</p>
-----------------------	--

Output signal













= relay energized

= relay de-energized

= lit

= unlit

L00-FTL2xxxx-07-05-xx-xx-001

Safety mode	Level	Output signal	LEDs green	red
Max.		 <div>3 4 5 6 7 8</div>		
		 <div>3 4 5 6 7 8</div>		
Min.		 <div>3 4 5 6 7 8</div>		
		 <div>3 4 5 6 7 8</div>		

L00-FTL5xxxx-04-05-xx-xx-003

Signal on alarm	Output signal on power failure or in the event of damaged sensor: relay de-energized
-----------------	--

Connectable load	<ul style="list-style-type: none">■ Loads switched via 2 floating change-over contacts (DPDT).■ $I_{\sim} \leq 6 \text{ A}$ (Ex de 4 A), $U_{\sim} \leq \text{AC } 253 \text{ V}$; $P_{\sim} \leq 1500 \text{ VA}$, $\cos \varphi = 1$, $P_{\sim} \leq 750 \text{ VA}$, $\cos \varphi > 0.7$■ $I_{=} \leq 6 \text{ A}$ (Ex de 4 A) to DC 30 V, $I_{=} \leq 0.2 \text{ A}$ to 125 V■ When connecting a low-voltage circuit with double insulation according to IEC 1010, the following applies: the sum of the voltages of the relay output and power supply is ≤ 300 V■ The electronic insert FEL52 DC-PNP is preferred for low DC load currents (e.g. when connecting to a PLC)■ Relay contact material: silver/nickel AgNi 90/10
------------------	--

Electronic insert FEL55 (8/16 mA)


Power supply

Supply voltage: DC 11 to 36 V
 Power consumption: < 600 mW
 Reverse polarity protection
 Overvoltage protection FEL55: overvoltage category III

Electrical connection

Two-wire connection for separate switching unit

For separate switching unit.
 Signal transmission 16/8 mA on two-wire cabling.
 For connection to programmable logic controllers (PLCs) for example,
 AI module 4 to 20 mA to EN 61131-2.
 Output signal jump from high to low current on point level.



L00-FTL5xxxx-04-05-xx-xx-000

Output signal

$$\sim 16 \text{ mA} = 16 \text{ mA} \pm 5 \%$$

$$\sim 8 \text{ mA} = 8 \text{ mA} \pm 6 \%$$



= lit



= unlit

L00-FTL2xxxx-07-05-xx-xx-000

Safety mode	Level	Output signal	LEDs	
			green	red
Max.		+ 2 $\xrightarrow{\sim 16 \text{ mA}}$ 1		
		+ 2 $\xrightarrow{\sim 8 \text{ mA}}$ 1		
Min.		+ 2 $\xrightarrow{\sim 16 \text{ mA}}$ 1		
		+ 2 $\xrightarrow{\sim 8 \text{ mA}}$ 1		

L00-FTL5xxxx-04-05-xx-xx-000

Signal on alarm

Output signal on power failure or in the event of damaged sensor: < 3.6 mA

Connectable load

- $R = (U - 11 \text{ V}) : 16.8 \text{ mA}$
 - $U = \text{connection voltage: DC 11 to 36 V}$
- Example: PLC with 250 Ω with 2-wire version

$$250 \Omega = (U - 11 \text{ V}) / 16.8 \text{ mA}$$

$$4.2 [\Omega / \text{A}] = U - 11 \text{ V}$$

$$U = 15.2 \text{ V}$$

Electronic insert FEL56 (NAMUR L-H edge)


Power supply Power consumption: < 6 mW at I < 1 mA; < 38 mW at I = 2.8 mA
Connection data interface: IEC 60947-5-6

Electrical connection **Two-wire connection for separate switching unit**

For connecting to isolating amplifiers acc. to NAMUR (IEC 60947-5-6), e.g. FTL325N, FTL375N from Endress+Hauser.
Output signal jump from low to high current on point level.




(L-H edge)

Connecting to multiplexer:
Set clock time to min. 2 s.















L00-FTL5xxxx-04-05-xx-en-004

Output signal

 = lit
 = flashes
 = unlit

L00-FTL5xxxx-07-05-xx-xx-002

Safety mode	Level	Output signal	LEDs	
			green	red
Max.		+ 0.6 ... 1.0 mA 2 → 1		
		+ 2.2 ... 2.8 mA 2 → 1		
Min.		+ 0.6 ... 1.0 mA 2 → 1		
		+ 2.2 ... 2.8 mA 2 → 1		

L00-FTL5xxxx-04-05-xx-xx-003

Signal on alarm Output signal in the event of damaged sensor: > 2.2 mA

Connectable load ■ See Technical Data of the isolating amplifier connected according to IEC 60947-5-6 (NAMUR)

Electronic insert FEL58 (NAMUR H-L edge)

Power supply

Power consumption: < 6 mW at I < 1 mA; < 38 mW at I = 3.5 mA
Connection data interface: IEC 60947-5-6


Electrical connection

Two-wire connection for separate switching unit


For connecting to isolating amplifiers as per NAMUR (IEC 60947-5-6), e.g. FTL325N, FTL375N from Endress+Hauser.
Output signal jump from high to low current on point level.

(H-L edge)

Additional function:
Test key on the electronic insert.
Pressing the key breaks the connection to the isolating amplifier.




 **Note!**
In Ex-d applications, the additional function can only be used if the housing is not exposed to an explosive atmosphere.

Connecting to multiplexer:
Set clock time to min. 2 s.















L00-FTL5xxxx-04-05-xx-xx-002

Output signal

 = lit
 = flashes
 = unlit

L00-FTL5xxxx-07-05-xx-xx-002

Safety mode	Level	Output signal	LEDs green yellow
Max.		+ 2.2 ... 3.5 mA 2 → 1	 
		+ 0.6 ... 1.0 mA 2 → 1	 
Min.		+ 2.2 ... 3.5 mA 2 → 1	 
		+ 0.6 ... 1.0 mA 2 → 1	 

L00-FTL5xxxx-04-05-xx-xx-007

Signal on alarm

Output signal in the event of damaged sensor: < 1.0 mA

Connectable load

- See Technical Data of the isolating amplifier connected according to IEC 60947-5-6 (NAMUR)
- Connection also to isolating amplifiers which have special safety circuits (I > 3.0 mA)

Electronics FEL58 (NAMUR H-L edge, in compact housing)

Power supply Power consumption: < 6 mW at I < 1 mA; < 38 mW at I = 3.5 mA
Connection data interface: IEC 60947-5-6

Electrical connection **Two-wire connection for separate switching unit**





For connecting to isolating amplifiers acc. to NAMUR (IEC 60947-5-6), e.g. FTL325N, FTL375N from Endress+Hauser. Output signal jump from high to low current on point level.

(H-L edge)

Additional function:
If the test magnet is held against the marking on the nameplate, the output signal is inverted.




Connecting to multiplexer:
Set clock time to min. 3 s.

The NAMUR interface has a defined power consumption rate. Thus, it is not possible to use the M12 connector with an integrated LED (52018763).













Connector	MAX	MIN
<div>FTL5#(H)- #####N3# (M12x1) 52018763</div> 		
<div>FTL5#(H)- #####N3# (M12x1) 52010285 / 52024216</div> 		
<div>FTL5#(H)- #####D3# (Pg11) or FTL5#(H)- #####E3# (NPT 1/2")</div> 		
<div>FTL5#(H)- #####C3#</div> 		

L00-FTL5xxxx-04-05-xx-en-009

Output signal

 = lit
 = flashes
 = unlit

L00-FTL5xxxx-07-05-xx-xx-002

Safety mode	Level	Output signal	LEDs green yellow
Max.		+ 2.2... 3.5 mA - 1 → 3	 
		+ 0.6... 1.0 mA - 1 → 3	 
Min.		+ 2.2... 3.5 mA - 1 → 2	 
		+ 0.6... 1.0 mA - 1 → 2	 

L00-FTL5xxxx-04-05-xx-xx-007a

Signal on alarm Output signal in the event of damaged sensor: < 1.0 mA

Connectable load

- See Technical Data of the isolating amplifier connected according to IEC 60947-5-6 (NAMUR)
- Connection also to isolating amplifiers which have special safety circuits (I > 3.0 mA)

Electronic insert FEL57 (PFM)

Power supply

Supply voltage: DC 9.5 to 12.5 V
 Current consumption: 10 to 13 mA
 Power consumption: < 150 mW
 Reverse polarity protection

Electrical connection

Two-wire connection for separate switching unit

For connecting to Endress+Hauser switching units Nivotester FTL320, FTL325P, FTL370, FTL372, FTL375P (also with proof test).

Output signal jump of the PFM signal from high to low frequency when sensor is covered. Switching between minimum/maximum safety in the Nivotester.


Additional function "proof test":
 After interruption of the power supply, a test cycle is activated which checks the sensor and electronics without any change in level.
 Approved for overfill protection acc. to WHG (German Water Resources Act).
 The following can be switched at the electronic insert:

– Standard (STD):

Corrosion of the fork unlikely;
 simulation approx. 8 s
 tuning fork exposed – covered – exposed.
 For proof testing, the Nivotester tests the sensor's level notification function.

– Extended (EXT):

Corrosion of the fork possible;
 Simulation approx. 41 s: tuning fork exposed – covered – corroded – exposed.
 For proof testing, the Nivotester tests the sensor's level notification function and fault notification (alarm) function.



L00-FTL5xxxx-04-05-xx-en-003


The check is activated and monitored at the switching unit.

The twin-core connecting cable (instrument cable) with a cable resistance of $\leq 25 \Omega$ per core is connected to the screw terminals (conductor cross-sections 0.5 to 2.5 mm / 0.02 to 0.1 in) in the connection compartment. Protective circuits against reverse polarity, HF influences and overvoltage peaks are installed.

Maximum cable length up to 1000 m (3281 ft).

A shielded connecting cable is recommended in the event of strong electromagnetic interference. Here the shielding must be connected to the sensor and the power supply.

Switching behavior of the connected device:












L00-FTL5xxxx-05-05-xx-en-000

* De-energized on power supply failure

Please note this switching response and function of the plant especially when replacing a Liquiphant incorporating electronic insert EL17Z or FEL37 with a Liquiphant M incorporating electronic insert FEL57.

Output signal



Safety mode	Level	Output signal (PFM)	LEDs green	LEDs yellow
		150 Hz 		
		50 Hz 		

L00-FTL5xxxx-04-05-xx-xx-008

Signal on alarm

Output signal on power failure or in the event of damaged sensor: 0 Hz

Connectable load

- Floating relay contacts in the connected switching unit Nivotester FTL320, FTL325P, FTL370, FTL372, FTL375P
- For contact load, see the Technical Data of the switching unit.

Electronic insert FEL50A (PROFIBUS PA)

Power supply

Bus voltage: DC 9 to 32 V

Bus current:

- 12.5 mA +/- 1.0 mA (software version: 01.03.00, hardware version: 02.00)
- 10.5 mA +/- 1.0 mA (software version: 01.03.00, hardware version: 01.00)


Electrical connection

Two-wire connection for power supply and data transfer


For connecting to PROFIBUS PA

Additional functions:

- Digital communication enables the representation, reading and editing of the following parameters:
Fork frequency, switch-on frequency, switch-off frequency, switch-on time and switch-off time, status, measured value, density switch.
- Matrix locking possible
- Switch to WHG mode possible (WHG approval)
- For a detailed description, see BA198F





L00-FTL5xxxx-04-05-xx-en-005















L00-FTL5xxxx-04-05-xx-en-006

Output signal

 = lit

 = unlit

L00-FTL2xxxx-07-05-
xx-xx-000

Setting	Level	LEDs		FEL50A
		green	yellow	
not inverted				OUT_D = 0 PA bus signal
				OUT_D = 1 PA bus signal
inverted				OUT_D = 0 PA bus signal
				OUT_D = 1 PA bus signal

L00-FTL5xxxx-04-05-xx-xx-000

Signal on alarm

- Failure information can be opened using the following interfaces:
Yellow LED flashing, status code, diagnostic code; see BA00198F

Electronic insert FEL50D (density)

Power supply


Frequency range: 300 to 1500 Hz
 Signal level: 4 mA
 Pulse height: 16 mA
 Pulse width: 20 µS


Electrical connection

Two-wire connection at Density Computer FML621

For connecting to the density and concentration computer FML621.

The output signal is based on pulse technology. With the aid of this signal, the fork frequency is constantly forwarded to the switching unit.

 **Caution!**
 Operation with other switching units, such as FTL325P, is not permitted. This electronic insert cannot be installed in devices that were originally used as a point level switch.



TI420Fen004

Signal on alarm

Output signal on power failure or in the event of damaged sensor: 0 Hz

Adjustment

In the Liquiphant M modular system, the option of an adjustment is also provided in addition to the electronics (see feature 60: "Accessories").

There are three types of adjustment:

Standard adjustment (see ordering information for additional option, basic version A)

- Here, two fork parameters are determined to describe the sensor characteristics, indicated in the adjustment report and provided with the product. These parameters must be transmitted to the Density Computer FML621.

Special adjustment (see ordering information for additional option, special adjustment, density H₂O (K) or special adjustment, density H₂O with 3.1 certificate (L))

- Here, three fork parameters are determined to describe the sensor characteristics, indicated in the adjustment report and provided with the product. These parameters must be transmitted to the Density Computer FML621. Greater accuracy is achieved with this type of adjustment (see also "Performance characteristics").

Field Adjustment

- During field adjustment, a density value actually determined by the customer is entered and the system is automatically adjusted to this value (wet adjustment).




Note!

More information on Liquiphant M Density is available in Technical Information TI00420F. This can be downloaded from www.endress.com => Download.

Operating principle

Measuring the density of a liquid medium in pipes and tanks. Also suitable for use in hazardous areas, and preferably for applications in the chemical and food industry.



- * Pressure and temperature information required depending on the application.
1. Liquiphant M sensor with electronic insert FEL50D (pulse output);
 2. Temperature sensor (e.g. 4 to 20 mA output);
 3. Pressure transmitter (4 to 20 mA output);
 4. Liquiphant density and concentration computer FML621 with display and operating unit

Light signals


LED	Symbol	Information
Yellow		Measurement valid
		Unstable process situation
		Maintenance required
Green		Power on
		Power off
Red		No fault
		Maintenance required
		Device failure

Connection and function

Connecting cables	<ul style="list-style-type: none"> ■ Electronic inserts: cross-section $\leq 2.5 \text{ mm}^2$ (14 AWG); strand in ferrule as per DIN 46228 ■ Protective ground in housing: cross-section $\leq 2.5 \text{ mm}^2$ (14 AWG) ■ External equipotential bonding connection on housing: cross-section $\leq 4 \text{ mm}^2$ (12 AWG)
Safety mode	<p>Minimum/maximum residual current safety selectable on electronic insert. (with FEL57 on Nivotester only)</p> <p>MAX = maximum safety: The output switches to the power fail response when the fork is covered For use with overfill protection for example</p> <p>MIN = minimum safety: The output switches to the power fail response when the fork is exposed For use with dry running protection for example</p>
Switching time	<p>When fork is covered: approx. 0.5 s When fork is exposed: approx. 1.0 s Additionally configurable for PROFIBUS PA: 0.5-60 s</p> <p>Other switching times available on request.</p>
Switch-on behavior	<p>When switching on the power supply, the output assumes the alarm signal. After $\leq 3 \text{ s}$ it assumes the correct switching mode (exception: FEL57)</p>

Performance characteristics

Reference operating conditions	<p>Ambient temperature: $23 \text{ }^{\circ}\text{C}$ ($73 \text{ }^{\circ}\text{F}$) Medium temperature: $23 \text{ }^{\circ}\text{C}$ ($73 \text{ }^{\circ}\text{F}$) Medium density (water): 1 g/cm^3 (SGU) Medium viscosity: $1 \text{ mm}^2/\text{s}$ (cSt) Medium pressure p_e: 0 bar (0 psi) Sensor mounting: vertical from above Density switch: to $> 0.7 \text{ g/cm}^3$ (SGU)</p>
---------------------------------------	---



L00-FTL5xxxx-06-05-xx-xx-031

* Switch point under reference operating conditions


Maximum measured error	Under reference operating conditions: max. $\pm 1 \text{ mm}$ (0.04 in)
Repeatability	0.1 mm (0.004 in)
Hysteresis	approx. 2 mm (0.08 in)
Influence of medium temperature	max. $+1.8$ to -2.8 mm (-50 to $+150 \text{ }^{\circ}\text{C}$ / -58 to $302 \text{ }^{\circ}\text{F}$)
Influence of medium density	max. $+4.8$ to -3.5 mm (0.5 to 1.5 g/cm^3 (SGU)) max. $+0.19$ to -0.14 in
Influence of medium pressure	max. 0 to -2.5 mm (-1 to 64 bar (-14.5 to 928 psi)) max. 0 to -0.1 in

Operating conditions

Installation

Installation instructions

Switch points Δ on the sensor depend on the mounting position, with reference to water, Density 1 g/cm³ (SGU), 23 °C (73 °F), p_e 0 bar (0 psi).




Note!
The switch points of the Liquiphant **M** are at other positions to those of the previous version Liquiphant **II**.

Examples of mounting

Examples of mounting with regard to the viscosity ν of the liquid and the tendency to form buildup


Optimum mounting, without problem even with high viscosity:

Position the fork so that the narrow edge of the tines is vertical to ensure that the liquid can run off easily.




With buildup on the tank walls:

* Ensure that there is sufficient distance between the buildup expected on the tank wall and the fork.



Mounting positions in the case of low viscosity up to 2000 mm²/s (cSt):


* Deburr the nozzle surfaces



L00-FTL5xxxx-11-05-xx-xx-en-003

Mounting in piping from 2"


Flow velocities up to 5 m/s for viscosity of 1 mm²/s (cSt) and density 1 g/cm³ (SGU).
(Check the function for other medium conditions.)



L00-FTL5xxxx-11-05-xx-xx-004


Dynamic load

Support the Liquiphant M FTL51(H) in the event of a severe dynamic load.



L00-FTL5xxxx-11-05-xx-xx-005


Ensure adequate space outside the tank for mounting, connection and configuration.



- Orientation**
- FTL50(H) and FTL51(H) with short pipe up to approx. 500 mm (19.7 in): any position
 - FTL51(H) with long pipe: vertical

Environment

Ambient temperature range Permitted ambient temperature T_a at the housing depending on the medium temperature T_p in the tank:



- * Additional temperature range for devices with a temperature spacer or pressure-tight feedthrough.
** Maximum ambient temperature with FEL50D/FEL50A in hazardous areas.

Storage temperature -50 to +80 °C (-58 to 176 °F)

Installation height as per IEC61010-1 Ed.3 Up to 2000 m (6600 ft) above sea level.
Can be extended up to 3000 m (9800 ft) above sea level if overvoltage protection is used, for example HAW562 or HAW569.

Climate class Climate protection to IEC 68, Part 2-38, Fig. 2a

Degree of protection

Types of housing	IP65	IP66*	IP67*	IP68*	IP69k	NEMA type**
Compact housing with valve connector Pg11/NPT ½	X	–	–	–	–	–
Compact housing with 5 m (16 ft) cable tail	–	X	–	X	–	–
Compact housing with M12x1 connector (52010285) 316L (metal)	–	X	–	X	–	–
Compact housing with elbowed connector (52024216) / L= 5 m (16 ft), without integrated LEDs	–	X	–	X	X	–
Compact housing with elbowed connector (52018763) / L= 5 m (16 ft), with integrated LEDs	–	X	–	X	X	–
Polyester housing F16	–	X	X	–	–	4X
Stainless steel housing F15	–	X	X	–	–	4X
Aluminum housing F17	–	X	X	–	–	4X
Aluminum housing F13****	–	X	–	X***	–	4X/6P
Stainless steel housing F27	–	X	–	X	–	4X/6P
Aluminum housing T13 with separate connection compartment (Ex d)	–	X	–	X***	–	4X/6P

* As per EN60529

** As per NEMA 250

*** only with M20 cable entry or G1/2 thread

**** F13 housing only in conjunction with XP or Ex d approval

Vibration resistance

As per IEC 68, parts 2-6 (10 to 55 Hz, 0.15 mm (0.01 in), 100 cycles)



In the event of increased vibrations, the following additional option is recommended: feature "060" version "P" 100 bar (1450 psi) process pressure.

Electromagnetic compatibility

Interference emission to EN 61326, Electrical Equipment Class B

Interference immunity to EN 61326; Annex A (Industrial) and NAMUR Recommendation NE 21 (EMC)

Medium conditions







Medium temperature	-50 to +150 °C (-58 to 302 °F); for exceptions, see "Process connections"
Thermal shock	≤ 120 °C/s (248 °F/s)
Medium pressure p_e	<div></div> <p>* Permitted pressure rating when the "100 bar (1450 psi)" option is selected (see "Product structure FTL51", feature 060, from → 43). See "Process connections" → 33 for exceptions. Canadian CRN approval: Additional details on maximum pressure values are available in the download area of the product page at "www.endress.com".</p> <p>Please refer to the standards listed for the permitted pressure values of the flanges at higher temperatures:</p> <ul style="list-style-type: none">■ pR EN 1092-1: 2005 With regard to their stability-temperature property, the materials 1.4435 and 1.4404 are identical and are grouped together in EN 1092-1 Tab. 18 under 13E0. The chemical composition of the two materials can be identical.■ ASME B 16.5 - 2013 Tab. 2-2.2 F316■ ASME B 16.5 - 2013 Tab. 2-3.8 N10276■ JIS B 2220 <p>The lowest value from the derating curves of the device and selected flange applies in each case.</p>
Test pressure	<p>$p_e = 64$ bar (928 psi):</p> <ul style="list-style-type: none">■ ≤ 100 bar (1450 psi) or 1.5 times the medium pressure p_e■ Sensor burst pressure at 200 bar (2900 psi) <p>$p_e = 100$ bar (1450 psi):</p> <ul style="list-style-type: none">■ ≤ 150 bar (2175 psi) or 1.5 times the medium pressure p_e■ Sensor burst pressure at 400 bar (5800 psi) <p> Note! The device function is restricted during pressure testing.</p>
State of aggregation	Liquid
Density	<p>0.7 g/cm³ (SGU) = delivery status</p> <p>0.5 g/cm³* (SGU) can be adjusted via switches</p> <p>* Density settings for the compact housing on request</p>
Viscosity	≤ 10,000 mm ² /s (cSt)
Solids content	≤ ø5 mm (0.2 in)
Lateral loading capacity	≤ 75 Nm

Mechanical construction

Design

Summary of all electrical and mechanical versions

Housing

					
L00-FTL5xxxx-03-05-xx-xx-019	L00-FTL5xxxx-03-05-xx-xx-001	L00-FTL5xxxx-03-05-xx-xx-002	L00-FTL5xxxx-03-05-xx-xx-031	L00-FTL5xxxx-03-05-xx-xx-033	L00-FTL5xxxx-03-05-xx-xx-004
Compact Pipe housing (316L)	F16 Polyester (PBT)	F15 Stainless steel (316L)	F17 Aluminum Housing coated	F27 Stainless steel (316L) F13 Aluminum (also for Ex d/XP), housing coated	T13 Aluminum with separate connection compartment (also Ex de and Ex d), housing coated

Plug-in electronic inserts to mount in the housing



L00-FTL5xxxx-03-05-xx-xx-000

FEL51*:	Two-wire AC connection
FEL52*:	Three-wire DC connection PNP
FEL54:	Universal current connection, 2 relay outputs
FEL55:	Output 16/8 mA for separate switching unit
FEL56:	Output 0.6 to 1.0 / 2.2 to 2.8 mA for separate switching unit (NAMUR)
FEL58*:	Output 2.2 to 3.5 / 0.6 to 1.0 mA for separate switching unit (NAMUR)
FEL57:	Output 150/50 Hz, PFM, for separate switching unit (Nivotester)
FEL50A:	Digital communication PROFIBUS PA
FEL50D:	Pulse output for Density Computer FML621

* Electronics also available as compact housing. The electronics cannot be exchanged!

Bushings (optional)

Temperature spacer and pressure-tight feedthrough




L00-FTL5xxxx-03-05-xx-xx-005

Process connections




L00-FTL5xxxx-03-05-xx-xx-006

G 3/4, DIN ISO 228/I
R 3/4, EN10226
NPT 3/4, ASME B 1.20.1
(AF 32)




L00-FTL5xxxx-03-05-xx-xx-007

G 1, DIN ISO 228/I
R 1, EN10226
NPT 1, ASME B 1.20.1
(AF 41)



L00-FTL5xxxx-03-05-xx-xx-008





Diverse
hygienic and
aseptic
connections



L00-FTL5xxxx-03-05-xx-xx-009

Flanges as per DIN,
ASME,
JIS
from DN 25 / 1"

Sensors

Compact, with extension pipe up to 3 m (up to 6 m on request) or special "length L II" (see →  33ff.)	II	Compact	Length L	Length L
				
		L00-FTL5xxxx-03-05-xx-xx-018		
p_e = bar/psi		64/928	64/928	64/928
			100/1450	100/1450

Dimensions


Dimensions in mm (in)!

Housing FTL50(H), FTL51(H) with sensor FTL50(H)

Compact housing, primarily for hygiene applications


c

1. 5 m cable
2. M12 connector
3. Pg11/NPT ½ connector




L00-FTL5xxxx-06-05-xx-xx-085

Polyester housing F16




L00-FTL5xxxx-06-05-xx-xx-086

F15 stainless steel housing primarily for hygiene applications




L00-FTL5xxxx-06-05-xx-xx-087

Aluminum housing F17




L00-FTL5xxxx-06-05-xx-xx-088

Stainless steel housing (316L) F27 Aluminum housing F13



L00-FTL5xxxx-06-05-xx-xx-089

Aluminum housing T13 with separate connection compartment



L00-FTL5xxxx-06-05-xx-xx-090

* See "Process connections"



Note!
The switch points of the Liquiphant **M** are at other positions to those of the previous version Liquiphant **II**.


Bushings: temperature spacer, pressure-tight feedthrough

Temperature spacer

Provides sealed insulation for the vessel and normal ambient temperatures for the housing.






Pressure-tight feedthrough

Protects the housing from pressures up to 100 bar (1450 psi) if the sensor is damaged. Provides sealed insulation for the vessel and normal ambient temperatures for the housing.







L00-FTL5xxxx-06-05-xx-xx-091




Process connections for FTL50(H) and FTL51(H)

Process connection		Dimensions	Accessories	Pressure Temperature
G 3/4 DIN ISO 228/1 with defined thread start; Flat seal to DIN 7603: supplied	GQ2 GQ6			≤ 100 bar / only FTL51 (≤ 1450 psi) ≤ 150 °C (302 °F)
G 3/4 DIN ISO 228/1 with defined thread start for flush-mounted installation in weld-in adapter	GQ2 GQ6		Weld-in adapter (with defined thread start) with silicone O-ring only FTL50, FTL50H See "Accessories" In conformity with FDA*	≤ 25 bar (363 psi) ≤ 150 °C (302 °F) ≤ 40 bar (580 psi) ≤ 100 °C (212 °F)
G 1 DIN ISO 228/1 Flat seal to DIN 7603: supplied	GR2 GR6			≤ 100 bar / only FTL51 (1450 psi) ≤ 150 °C (302 °F)
G 1 DIN ISO 228/1 with defined thread start With seal surface for flush-mounted installation in weld-in adapter	GW2		Weld-in adapter (with defined thread start) with silicone O-ring See "Accessories" In conformity with FDA*	≤ 25 bar (363 psi) ≤ 150 °C (302 °F) ≤ 40 bar (580 psi) ≤ 100 °C (212 °F)
NPT 3/4 ASME B 1.20.1 or R 3/4 DIN/EN 10226	GM2 GM6 GE2 GE6			≤ 100 bar / only FTL51 (1450 psi) ≤ 150 °C (302 °F)

Process connection		Dimensions	Accessories	Pressure Temperature
NPT1 ASME B 1.20.1 or R 1 DIN/EN 10226	GN2 GN6 GF2 GF6			≤ 100 bar / only FTL51 (1450 psi) ≤ 150 °C (302 °F)
* FDA-compliant material in accordance with 21 CFR Part 177.2600 (silicone)				
Flanges ASME B 16.5 EN 1092-1 (DIN 2527 B) JIS B2220	A## B## C## F## N## K##		Seal depending on design installed on site	See nominal pressure of flange, however ≤ 100 bar (1450 psi) (only FTL51) ≤ 150 °C (302 °F)
For higher chemical-resistance, AlloyC22-plated flanges are available. The flange carrier material is made of 316L and is welded with a 2 to 3 mm (0.08 to 0.12 in) thick AlloyC22 disk.				
Tri-Clamp ISO 2852 DN25-38 (1 to 1 1/2") DIN 32676 DN25-40 ø D = 50.5 mm (1.99 in) ISO 2852 DN40-51 (2") DIN 32676 DN50 ø D = 64.0 mm (2.52 in)	TC2 TE2		Clamping ring and front seal installed on site**	≤ 25 bar (363 psi) ≤ 150 °C (302 °F)
Mounting with NA connector only in conjunction with T13, F13 and compact housing. Other housings on request.				
Threaded pipe joint DN 32 DN 40 DN 50 DIN 11851 with thread adapter nut	MA2 MC2 ME2		Sealing ring with collar, installed on site**	DN 32, DN 40: ≤ 40 bar (580 psi) up to 100 °C (212 °F) ≤ 25 bar (363 psi) up to 140 °C (284 °F) DN 50: ≤ 25 bar (363 psi) ≤ 140 °C (284 °F)
Flush-mounted for weld-in adapter Factory standard Endress+Hauser with silicone seal and thread adapter nut: supplied	EE2		Weld-in adapter (fork can be positioned) See "Accessories" In conformity with FDA*	≤ 40 bar (580 psi) ≤ 100 °C (212 °F) ≤ 25 bar (363 psi) ≤ 150 °C (302 °F)
Aseptic DN 50 DIN 11864-1 Form A for pipe DIN 11850 with thread adapter nut	HE2		sealing ring installed on site**	≤ 25 bar (363 psi) ≤ 140 °C (284 °F)

Process connection		Dimensions	Accessories	Pressure Temperature
DRD With clamped flange	PE2		Welding flange with PTFE flat seal (fork can be positioned) See "Accessories" (or installed on site)** In conformity with FDA*	≤ 40 bar (580 psi) ≤ 100 °C (212 °F) ≤ 25 bar (363 psi) ≤ 150 °C (302 °F)
* FDA-compliant material in accordance with 21 CFR Part 177/2600 (silicone), 21 CFR Part 177.1550 (PTFE) ** The maximum temperature and the maximum pressure are dependent on the clamping ring used and the seal used. The lowest value applies in each case.				
SMS 2" (DN 51) with thread adapter nut	UE2		sealing ring installed on site**	≤ 25 bar (363 psi) ≤ 140 °C (284 °F)
Varivent for piping \geq DN 65 \geq O.D. 3" \geq I.P.S. 3"	WE2		Clamping ring and O-ring seal, installed on site**	However, see specification as per Tuchenhausen VARIVENT-Inline housing: ≤ 25 bar (363 psi) ≤ 150 °C (302 °F)
Ingold fitting DN 25 Fitting length 46 mm (2.52 in) Thread adapter nut G 1 ¼ with O-ring seal, EPDM (FDA-compliant, USP Class VI*)	TT2			≤ 16 bar (232 psi) ≤ 150 °C (302 °F)
* FDA-compliant material in accordance with 21 CFR Part 177/2600 (EPDM) ** The maximum temperature and the maximum pressure are dependent on the clamping ring used and the seal used. The lowest value applies in each case.				

Sensor length L for FTL51 and FTL51H, depending on process connection

Thread: G ¾ G 1	Thread: NPT ¾ NPT1 R ¾ R 1	Flanges and flange-like process connections
		
L00-FTL5xxxx-06-05-xx-xx-107	L00-FTL5xxxx-06-05-xx-xx-017	L00-FTL5xxxx-06-05-xx-xx-018
From seal surface of thread adapter	From lower edge of thread	
Customized length L: ■ 148 mm to 3000 mm (6 to 115 in); special version (TSP) on request up to 6000 mm (235 in) ■ Length tolerances L: < 1 m (-5 mm), 1 to 3 m (-10 mm) / < 3.3 ft (-0.2 in), 3.3 to 9.8 ft (-0.39 in)		



Note!

The switch points of the Liquiphant M are at other positions to those of the previous version Liquiphant II.

Special length "L II":

With vertical mounting from above the same switch point as for the Liquiphant II
FTL360, FTL365, FDL30, FDL35

"L II" depends on process connection:

L = 115 mm (4.53 in) for flanges and flange-like process connections

L = 99 mm (3.9 in) for threads NPT and R (BSPT)

L = 118 mm (4.65 in) for threads G1 (BSP 1)

L = 115 mm (4.53 in) for threads G ¾ (BSP ¾)

L = 104 mm (4.09 in) for flush-mounted 1" (Endress+Hauser)

Weights

See "Ordering information" → 43ff

Materials and surfaces

Material specifications as per AISI and DIN-EN.

Parts in contact with process

- Process connection and extension pipe:
 - FTL5x → 316L (1.4404 or 1.4435) optional 2.4602 (AlloyC22)
 - FTL5xH → 316L (1.4435)
- Tuning fork: 316L (1.4435) optional 2.4602 (AlloyC22)
- Flanges: 316L (1.4404)
- Flange plating: AlloyC22
- Flat seal for process connection G ¾ or G 1: elastomer fiber, asbestos-free

Surface roughness

Choice of mechanically polished surface roughness (version → probe length → type):

- Ra < 1.5 µm (59.1 µin), with EHEDG approval
- Ra < 0.3 µm (11.8 µin), 3-A and EHEDG approval and CoC-ASME-BPE



Note!

The surface is electropolished if the additional option "B"

(CoC - ASME BPE) is selected in addition to surface roughness quality Ra < 0.3 µm (11.8 µin). The

surface roughness is then: $R_a < 0.38 \mu\text{m}$ (15.0 μin).

With this combination, the wetted parts are made of 316L (1.4435) in accordance with BN2 (delta-ferrite content $< 1 \%$).

Parts with no process contact

- Tuning fork/housing seal: EPDM
- Temperature spacer: 316 L (1.4435)
- Pressure-tight feedthrough: 316L (1.4435)
- Ground terminal on housing (external): 316L (1.4404)
- Cable glands
 - Housing F13, F15, F16, F17: polyamide (PA)
 - With B or C approval (→ 43 ordering information): nickel-plated brass
 - Housing F27: polyamide PA, with approval "B" or "C" 316L (1.4435)
 - Housing T13: nickel-plated brass
- Polyester housing F16: PBT-FR with PBT-FR cover or with PA12 transparent cover
 - Cover seal: EPDM
 - Nameplate glued: polyester film (PET)
 - Pressure compensation filter: PBT-GF20
- Stainless steel housing F15: 316L (1.4404)
 - Cover seal: silicone
 - Safety claw: 304 (1.4301)
 - Pressure compensation filter: PBT-GF20, PA
- Aluminum housing F17/F13: EN-AC-ALSi10Mg, plastic-coated
 - Nameplate: aluminum, anodized
 - Cover seal: EPDM
 - Safety claw: nickel-plated brass
 - Pressure compensation filter: silicone
- Stainless steel housing F27: 316L
 - Nameplate: 316L (1.4404)
 - Cover seal: FVMQ (optional: EPDM seal available as spare part)
 - Safety claw: 316L (1.4435)
- Aluminum housing T13: EN-AC-ALSi10Mg, plastic-coated,
 - Nameplate: aluminum, anodized
 - Cover seal: EPDM
 - Safety claw: nickel-plated brass
- Compact housing (valve connector or M12 connector): 316L (1.4435)

Process connections

- Parallel thread G $\frac{3}{4}$, G 1 to DIN ISO 228/1 with flat seal to DIN 7603
- Tapered thread R $\frac{3}{4}$, R 1 to EN10226
- Tapered thread $\frac{3}{4}$ -14 NPT, 1 - 1 $\frac{1}{2}$ NPT as per ASME B 1.20.1
- Flush-mounted installation with weld-in adapter to factory standard Endress+Hauser (G $\frac{3}{4}$, G 1)
- Flush-mounted installation with weld-in adapter to factory standard Endress+Hauser (1"), sensor can be positioned
- Tri-Clamp 1 $\frac{1}{2}$ ", 2" to ISO 2852
- Threaded pipe joint DN 32, 40, 50 to DIN 11851
- Aseptic connection DN 50 to DIN 11864-1
Form A for pipe DIN 11850
- SMS connection 2" (DN 51)
- DRD flange
- Varivent® DN 50 (50/40) to factory standard Tuchenhausen
- Flanges: as per EN/DIN 1092-1 from DN 25, as per ASME B 16.5 from 1", as per JIS B2220 (RF)
- Ingold DN25 fitting length 46 mm (1.81 in) with thread adapter nut G1 $\frac{1}{4}$

Further details at Ordering information → 43.

Human interface

Electronic inserts

With FEL51, FEL52, FEL54, FEL55:

- 2 switches for safety mode and density change
- green LED to indicate operational status
- red LED to indicate the switching status, flashes in the event of corrosion damage on sensor or if the electronics are defective

With FEL56:

- 2 switches for safety mode and density change
- green LED flashes to indicate operational status
- red LED to indicate the switching status, flashes in the event of corrosion damage on sensor or if the electronics are defective

With FEL57:

- 2 switches for density change and Testing
- green LED to indicate operational status
- yellow LED to indicate the covered status, flashes in the event of corrosion damage on sensor or if the electronics are defective

With FEL58:


- 2 switches for safety mode and density change
- green LED
 - flashes quickly to indicate operational status,
 - flashes slowly in the event of corrosion damage to the sensor or if the electronics are defective
- yellow LED to indicate the switching status, Test key – breaks the cable connection

With FEL50A:

- 8 switches for configuring the device address
- green LED to indicate operational status, pulsing to indicate communication;
- yellow LED to indicate the switching status, flashes in the event of corrosion damage on sensor or if the electronics are defective

With FEL50D:


- yellow LED: to indicate the validation of the measurement
- green LED: to indicate the operational status
- red LED: to indicate faults




L00-FTL5xxxx-03-05-xx-xx-en-001



L00-FTL5xxxx-03-05-xx-xx-en-013



L00-FTL5xxxx-03-05-xx-xx-en-002



TI328Fox004


Compact housing

Function test with test magnet

Versions AC, DC-PNP and NAMUR:

During the test, the current state of the electronic switch is reversed.


Hold the test magnet against the marking on the nameplate: The switching status is changed.



L00-FTL5xxxx-19-05-xx-xx-001

Light signals

Versions AC and DC-PNP with valve connector or cable tail



L00-FTL5xxxx-07-05-xx-xx-005

Green light (gn) lights up (AC/DC):

Liquiphant M is connected to the power supply and is operational.

Green light (gn) flashing (NAMUR):

Liquiphant M is connected to the power supply and is operational.

Red light (rd) lights up (AC/DC):

MAX application mode (overflow protection): sensor is immersed in liquid.

MIN application mode (dry running protection): sensor is not immersed in liquid.


Yellow light (ye) lights up (NAMUR):

MAX application mode (overflow protection): sensor is not immersed in liquid.

MIN application mode (dry running protection): sensor is immersed in liquid.

Red light (rd) flashing (AC/DC):

Liquiphant M has detected a fault.

Version NAMUR and DC-PNP with M12x1 round connector 316L

L00-FTL50xxx-07-05-xx-xx-003

Green light (gn) lights up (DC-PNP):

Liquiphant M is connected to the power supply and is operational.

Green light (gn) flashing with 1 Hz (NAMUR):

Liquiphant M is connected to the power supply and is operational.

Yellow light (ye) lights up (DC-PNP):

Sensor is immersed in liquid.

Yellow light (ye) lights up (NAMUR):

MAX application mode (overflow protection): sensor is not immersed in liquid.


MIN application mode (dry running protection): sensor is immersed in liquid.

Red light (rd) flashing (DC-PNP):

Liquiphant M has detected a fault.

Green light (gn) flashing with 0.3 Hz (NAMUR):

Liquiphant M has detected a fault.

Version DC-PNP with M12x1 round connector 316L

L00-FTL50xxx-07-05-xx-xx-004

Green light (gn) lights up:

Liquiphant M is connected to the power supply and is operational.

Yellow light (ye 1) lights up:

MAX application mode (overflow protection): sensor is not immersed in liquid.

MIN application mode (dry running protection): sensor is not immersed in liquid.

Yellow light (ye 2) lights up:

MAX application mode (overflow protection): sensor is immersed in liquid.

MIN application mode (dry running protection): sensor is immersed in liquid.

Green light (gn) lights up, both yellow lights (ye 1+2) do not light up:

Liquiphant M has detected a fault.

Operating concept

Onsite configuration

Certificates and approvals

CE mark

The measuring system meets the legal requirements of the applicable EC Directives. These are listed in the corresponding EC Declaration of Conformity along with the standards applied.

Endress+Hauser confirms successful testing of the device by affixing to it the CE mark.


C-tick mark

The measuring system complies with the EMC requirements of the "Australian Communications and Media Authority (ACMA)".

General approvals

The following approvals are available for Liquiphant M FTL50H, FTL51H:

- EHEDG: certification (from TNO, The Netherlands), Report No. V99.394:
- 3A: 3A certificate (USA), Authorization no. 459: 74-06 Sensors and Sensor Fittings and Connections
- Certificate of Compliance as per ASME BPE-2012. (Order code: additional option = B)

Process connections	Order code			ASME BPE + CoC	
				Ra (µm)	
				< 0.38	< 1.5
Thread ISO228 G3/4, 316L, installation Thread ISO228 G1, 316L, installation Accessories: weld-in adapter	GQ2 GW2	X	X	–	X
Tri-Clamp ISO2852 DN25-38 (1 to 1-1/2"), 316L Tri-Clamp ISO2852 DN40-51 (2"), 316L	TC2 TE2	X	X	X	X
DIN11851 DN32 PN25 slotted nut, 316L DIN11851 DN40 PN25 slotted nut, 316L DIN11851 DN50 PN25 slotted nut, 316L	MA2 MC2 ME2	X	X	X	X
Flush-mounted, 316L, installation Accessories, weld-in adapter	EE2	X	X	X	X
DIN11864-1 A DN50 pipe DIN11850, Slotted nut, 316L	HE2	X	X	X	X
DRD 65mm, 316L	PE2	X	–	–	X
SMS 2" PN25, 316L	UE2	X	X	X	X
Varivent N pipe DN65-162 PN10, 316L	WE2	X	X	X	X
Ingold fitting 25x46mm, 316L	TT2	–	–	X	–

**Warning!**

To avoid risk of contamination, install according to the "Hygienic Equipment Design Criteria (HDC)" as stated in the Subgroup Design Principles of the EHEDG, Doc. 8, July 1993.

The flow of liquid during cleaning is important and should be in compliance with the HDC.

**Note!**

- For CIP (Clean in Place) and SIP (Sterilize in Place) processes the pressure and temperature specifications of the process connections must be observed.
- Suitable fittings and seals must be used to ensure hygiene-compliant design according to 3A, EHEDG, ASME BPE etc.
- Surfaces with ASME-BPE option: Ra < 0.38 µm (< 15 µin) electropolished and passivated or Ra < 1.5 µm (59 µin) mechanically polished.

CRN approval

Versions with a CRN approval (Canadian Registration Number) are marked with a "*" in ordering information feature 20 "process connection" (s. Seite 43 ff.). CRN-approved devices are assigned the registration number 0F10525.5C on the nameplate.

Process seal according to ANSI/ISA 12.27.01

Practice in North America for the installation of process seals

Endress+Hauser devices are designed as either single seal or dual seal devices with an alarm in accordance with ANSI/ISA 12.27.01. This means that the user does need to install for an external secondary process seal in the thermowell which is required in ANSI/NFPA 70 (NEC) and CSA 22.1 (CEC). These devices comply with installation practice in North America and enable very safe, low-cost installation in pressurized applications with hazardous media.

Further information is provided in the Safety Instructions (XA) for the specific device → 58 ff.

Product	Type	Max. process pressure	Marking	Listing
Liquiphant M	FTL50-S/T##...	64 bar (928 psi)	Single Seal	CSA/FM
	FTL50-P/Q/R##...			
	FTL51-S/T##...	64/100 bar	Single Seal	CSA/FM
	FTL51-P/Q/R##...	(928/1450 psi)		
	FTL50H-S/T##...	64 bar (928 psi)	Single Seal	CSA/FM
	FTL50H-P/Q/R##...			
	FTL51H-S/T##...	64 bar (928 psi)	Single Seal	CSA/FM
	FTL51H-P/Q/R##...			

Other certificates

- Material certificate as per EN 10204/3.1 for all wetted parts NACE MR0175/MR0103, AD2000
- Leak detection system in conjunction with WHG approval
Approval number: Z-65.40-446 (see also "Ordering information" s. Seite 43 ff.)
- TSE Certificate of Suitability
The following applies to wetted device components:
 - They do not contain any materials derived from animals.
 - No additives or operating materials derived from animals are used in production or processing.

**Note!**

Wetted device components are listed in the "Mechanical construction" (→ 30 ff.) and "Ordering information" (→ 43 ff.) sections.

Manufacturer declarations

The following documents are optionally available to order with the device:

- FDA conformity
- TSE-free: Materials not derived from animals
- Regulation (EC) no. 2023/2006 (GMP)
- Regulation (EC) No. 1935/2004 materials in contact with food

The applicable European guidelines and standards can be found in the relevant EU Declarations of Conformity.

Regulation (EC) no. 10/2011: The regulation on plastic materials does not apply to the Liquiphant FTL5x, as the wetted materials are made exclusively of stainless steel.

The silicone seals supplied comply with BFR recommendation XV (commodities based on silicones from the Federal Institute for Risk Assessment - BFR), and the EPDM seals provided comply with BFR recommendation XXI (commodities based on natural and synthetic rubber).

Use in hazardous zones

Pay particular attention to the information provided in the documentation: Safety Instructions, Control Drawings etc. → 58

ASME B 31.3

Design and materials in accordance with ASME B31.3 The welding seals are through-penetration welded and comply with ASME Boiler and Pressure Vessel Code Section IX and EN ISO 15614-1.

Pressure equipment directive

The pressure equipment directive 97/23/EC does not apply to the Liquiphant FTL5x, as it does not have a pressurized housing in accordance with Article 1, Paragraph 2.1.4 of the directive.

Ordering information



Note!

Versions that are mutually exclusive are not indicated in this list.

**Liquiphant M FTL50, FTL51
product structure**

Design		Basic weight	
FTL50	Compact		0.6 kg
FTL51	With extension pipe		0.6 kg
10	Approval:		
	A Non-hazardous area B ATEX II 3G Ex nC IIC T6, WHG, ATEX II 3D Ex tc IIIC T85°C, NEPSI II 3G Ex nC IIC T6 C ATEX II 3G Ex nA IIC T6, WHG, ATEX II 3D Ex tc IIIC T85°C, NEPSI II 3G Ex nA IIC T6 D Non-hazardous area, WHG E ATEX II 1/2G Ex de IIC T6, WHG F ATEX II 1/2GD Ex ia IIC T6, WHG/IECEx G ATEX II 1/2GD Ex ia IIC T6/IECEx Zone0/1 H ATEX II 1G Ex ia IIC T6 I ATEX II 1/2G Ex de IIC T6/IECEx Zone0/1 J ATEX II 1G Ex ia IIC T6, WHG K ATEX II 1/2G Ex d IIC T6/IECEx Zone0/1 L ATEX II 1/2G Ex d IIC T6, WHG M NEPSI Ex ia IIC T6 N NEPSI Ex d IIC T6 P FM IS Cl.I,II,III Div.1 Gr.A-G, Zone 0,1,2,20,21,22 Q FM XP Cl.I,II,III Div.1 Gr.B-G, Gr.A-G if E5 housing selected, Zone 1,2 R FM NI Cl.I Div.2 Gr.A-D, Zone 0,1,2,20,21,22 S CSA C/US IS Cl I,I,II,III Div.1 Gr.A-G, Zone 0,1,2 T CSA C/US XP Cl I,I,II,III Div.1 Gr.A-G, Zone 1,2 U CSA C/US General Purpose V TIIS Ex ia IIC T3 W TIIS Ex d IIB T3 7 TIIS Ex d IIC T3 8 TIIS Ex d IIC T6 1 INMETRO Ex ia IIC T6 Ga/Gb 2 INMETRO Ex d IIC T6 Ga/Gb 3 INMETRO Ex de IIC T6 Ga/Gb Y Special version, TSP-No. to be spec.		
20	Process connection:		Additional weight
	Note! For 100 bar (1450 psi) process pressure, select the appropriate option under "Additional option"		
	GQ2	G ¾ 316L Thread ISO 228	
	Installation > accessories: weld-in adapter		
	GQ6	G ¾ AlloyC22 Thread ISO 228	
	GR2	G 1 316L Thread ISO 228	0.2 kg
	GR6	G 1 AlloyC22 Thread ISO 228	0.2 kg
	GW2*	G 1 316L Thread ISO 228	0.2 kg
	Installation > accessories: weld-in adapter		
	GM2*	NPT ¾ 316L Thread ASME	
	GM6	NPT ¾ AlloyC22 Thread ASME	
	GN2*	NPT1 316L Thread ASME	0.2 kg
	GN6	NPT1 AlloyC22 Thread ASME	0.2 kg
	GE2	R ¾ 316L Thread EN10226	
	GE6	R ¾ AlloyC22 Thread EN10226	
	GF2	R 1 316L Thread EN10226	0.2 kg

20	Process connection:					Additional weight
	GF6	R 1		AlloyC22	Thread EN10226	0.2 kg
	BA2	DN32	PN6 A	316L	Flange EN 1092-1 (DIN 2527 B)	1.2 kg
	BB2	DN32	PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	2.0 kg
	BC2	DN40	PN6 A	316L	Flange EN 1092-1 (DIN 2527 B)	1.4 kg
	BD2	DN40	PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	2.4 kg
	BE2	DN50	PN6 A	316L	Flange EN 1092-1 (DIN 2527 B)	1.6 kg
	BG2	DN50	PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	3.2 kg
	BH2	DN65	PN6 A	316L	Flange EN 1092-1 (DIN 2527 B)	2.4 kg
	BJ2	DN50	PN100 A	316L (FTL51)	Flange EN 1092-1 (DIN 2527 B)	
	BK2	DN65	PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	4.3 kg
	BM2	DN80	PN10/16 A	316L	Flange EN 1092-1 (DIN 2527 B)	4.8 kg
	BN2	DN80	PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	5.9 kg
	BO2	DN100	PN10/16 A	316L	Flange EN 1092-1 (DIN 2527 B)	5.6 kg
	BR2	DN100	PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	7.5 kg
	B12	DN80	PN100 A	316L (FTL51)	Flange EN 1092-1 (DIN 2527 B)	
	B82	DN25	PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	1.4 kg
	CA2	DN32	PN6 B1	316L	Flange EN 1092-1 (DIN 2527 C)	1.1 kg
	CA6	DN32	PN6 B1	AlloyC22 >316L	Flange EN 1092-1 (DIN 2527)	1.1 kg
	CE2	DN50	PN6 B1	316L	Flange EN 1092-1 (DIN 2527 C)	1.5 kg
	CE6	DN50	PN6 B1	AlloyC22 >316L	Flange EN 1092-1 (DIN 2527)	1.5 kg
	CG2	DN50	PN25/40 B1	316L	Flange EN 1092-1 (DIN 2527 C)	2.9 kg
	CG6	DN50	PN25/40 B1	AlloyC22 >316L	Flange EN 1092-1 (DIN 2527)	2.9 kg
	CJ2	DN50	PN100 B2	316L (FTL51)	Flange EN 1092-1 (DIN 2527)	
	CN2	DN80	PN25/40 B1	316L	Flange EN 1092-1 (DIN 2527 C)	5.2 kg
	CN6	DN80	PN25/40 B1	AlloyC22 >316L	Flange EN 1092-1 (DIN 2527)	5.2 kg
	CQ2	DN100	PN10/16 B1	316L	Flange EN 1092-1 (DIN 2527 C)	5.3 kg
	CQ6	DN100	PN10/16 B1	AlloyC22 >316L	Flange EN 1092-1 (DIN 2527)	5.3 kg
	C12	DN80	PN100 B2	316L (FTL51)	Flange EN 1092-1 (DIN 2527)	
	C82	DN25	PN25/40 B1	316L	Flange EN 1092-1 (DIN 2527 C)	1.3 kg
	C86	DN25	PN25/40 B1	AlloyC22 >316L	Flange EN 1092-1 (DIN 2527)	1.3 kg
	DG2	DN50	PN40 B1	316L	Flange EN 1092-1 (DIN 2526 D)	
	DN2	DN80	PN40 B1	316L	Flange EN 1092-1 (DIN 2526 D)	
	D82	DN25	PN40 B1	316L	Flange EN 1092-1 (DIN 2526 D)	
	EG2	DN50	PN25/40 E	316L	Flange EN 1092-1	2.6 kg
	FG2	DN50	PN40 C	316L	Flange EN 1092-1 (DIN 2512 F)	2.6 kg
	NG2	DN50	PN40 D	316L	Flange EN 1092-1 (DIN 2512 N)	2.9 kg
	AA2*	1¼"	150 lbs	RF 316/316L	Flange ASME B16.5	1.2 kg
	AB2*	1¼"	300 lbs	RF 316/316L (FTL51)	Flange ASME B16.5	2.0 kg
	AC2*	1½"	150 lbs	RF 316/316L	Flange ASME B16.5	1.5 kg
	AD2*	1½"	300 lbs	RF 316/316L (FTL51)	Flange ASME B16.5	2.7 kg

20	Process connection:						Additional weight
	AE2*	2"	150 lbs	RF	316/316L	Flange ASME B16.5	2.4 kg
	AE6	2"	150 lbs	RF	AlloyC22 >316/316L	Flange ASME B16.5	2.4 kg
	AF2*	2"	300 lbs	RF	316/316L	Flange ASME B16.5	3.2 kg
	AG2*	2"	600 lbs	RF	316/316L (FTL51)	Flange ASME B16.5	4.2 kg
	AJ2*	2½"	300 lbs	RF	316/316L (FTL51)	Flange ASME B16.5	4.8 kg
	AL2*	3"	150 lbs	RF	316/316L	Flange ASME B16.5	4.9 kg
	AM2*	3"	300 lbs	RF	316/316L (FTL51)	Flange ASME B16.5	6.8 kg
	AM6	3"	300 lbs	RF	AlloyC22 >316/316L	Flange ASME B16.5	6.8 kg
	AN2*	3"	600 lbs	RF	316/316L (FTL51)	Flange ASME B16.5	
	AP2*	4"	150 lbs	RF	316/316L	Flange ASME B16.5	7.0 kg
	AQ2*	4"	300 lbs	RF	316/316L (FTL51)	Flange ASME B16.5	11.5 kg
	AQ6	4"	300 lbs	RF	AlloyC22 >316/316L	Flange ASME B16.5	11.5 kg
	AR2*	4"	600 lbs	RF	316/316L (FTL51)	Flange ASME B16.5	17.3 kg
	A82*	1"	150 lbs	RF	316/316L	Flange ASME B16.5	1.0 kg
	KA2	10 K 25 A		RF	316L	Flange JIS B2220	
	KC2	10 K 40 A		RF	316L	Flange JIS B2220	
	KE2	10 K 50 A		RF	316L	Flange JIS B2220	1.7 kg
	KE6	10 K 50 A		RF	AlloyC22 >316L	Flange JIS B2220	1.7 kg
	KL2	10 K 80 A		RF	316L	Flange JIS B2220	
	KP2	10 K 100 A		RF	316L	Flange JIS B2220	
	TC2*	DN25-38 (1 to 1½")			316L	ISO 2852 Tri-Clamp	
	TE2*	DN40-51 (2")			316L	ISO 2852 Tri-Clamp	0.1 kg
	YY9	Special version					
		* With CRN approval.					
30	Probe length; Type:						
	FTL50						
	AA	Compact;			Ra <3.2 µm/126 µin		
	IA	Compact;			Temperature spacer		0.6 kg
	QA	Compact;			Pressure-tight feedthrough		0.7 kg
	FTL51						
	BB mm;	316L**		Ra <3.2 µm/126 µin		
	BE mm;	Alloy**		Ra <3.2 µm/126 µin		
	CB inch;	316L**		Ra <3.2 µm/126 µin		
	CE inch;	Alloy**		Ra <3.2 µm/126 µin		2.3 kg/100 in
	DB	Length: type II*;	316L		Ra <3.2 µm/126 µin		0.1 kg
	DE	Length: type II*;	Alloy		Ra <3.2 µm/126 µin		0.1 kg
	JB mm;	316L**		+ Temperature spacer		0.9 kg/m +0.6 kg
	JE mm;	Alloy**		+ Temperature spacer		0.9 kg/m +0.6 kg
	KB inch;	316L**		+ Temperature spacer		2.3 kg/100 in +0.6 kg
	KE inch;	Alloy**		+ Temperature spacer		2.3 kg/100 in +0.6 kg
	LB	Length: type II*;	316L		+ Temperature spacer		0.1 kg +0.6 kg
	LE	Length: type II*;	Alloy		+ Temperature spacer		0.1 kg +0.6 kg
	RB mm;	316L**		+ Pressure-tight feedthrough		0.9 kg/m +0.7 kg
	RE mm;	Alloy**		+ Pressure-tight feedthrough		0.9 kg/m +0.7 kg
	SB inch;	316L**		+ Pressure-tight feedthrough		2.3 kg/100 in +0.7 kg
	SE inch;	Alloy**		+ Pressure-tight feedthrough		2.3 kg/100 in +0.7 kg
	TB	Length: type II*;	316L		+ Pressure-tight feedthrough		0.1 kg +0.7 kg
	TE	Length: type II*;	Alloy		+ Pressure-tight feedthrough		0.1 kg +0.7 kg
	YY	Special version					
		*) Replacing devices: when vertically mounting a Liquiphant M FTL51 with length II, the switch point is at the same height as for a Liquiphant II FTL360, FTL365, FDL30, FDL35. See also Seite 36 "L II" depends on process connection.					
		**) Order 3001 to 6000 mm (116 to 235 in) via yy					

40					Electronics; output:			
				A	FEL50A	PROFIBUS PA		
				D	FEL50D	Density/concentration without WHG approval (Germany)		
				1	FEL51*	2-wire,	AC 19 to 253 V	
				2	FEL52*	3-wire PNP,	DC 10 to 55 V	
				4	FEL54	Relay DPDT,	AC 19 to 253 V, DC 19 to 55 V	
				5	FEL55	8/16 mA,	DC 11 to 36 V	
				6	FEL56	NAMUR (L-H signal)		
				7	FEL57	2-wire PFM		
				8	FEL58*	NAMUR + test keys (H-L signal)		
				9	Special version			
					*) Also available in compact housing			
50					Housing; cable entry:			
				C3	Compact 316L	IP66/68;	Cable 5 m	
				D3	Compact 316L	IP65;	Plug Pg11	ISO4400
				E1	F27 316L	NEMA 4X/6P;	Thread NPT ¾	
				E3	Compact 316L Hygiene	NEMA4X;	Plug NPT ½	ISO4400
				N3	Compact 316L Hygiene	IP66/68;	M12 connector	
				E4	F16 Polyester	NEMA4X;	Thread NPT ½	
				E5	F13 Alu F17 Alu	NEMA4X/6P; NEMA4X	Thread NPT ¾	0.5 kg
				E6	F15 316L hygiene	NEMA4X;	Thread NPT ½	0.1 kg
				E7	T13 Alu	NEMA4X/6P;	Thread NPT ¾	0.9 kg
					Separate connection compartment			
				F1	F27 316L	IP66/68	Thread G1/2	
				F4	F16 Polyester	IP66/67;	Thread G ½	
				F5	F13 Alu F17 Alu	IP66/68; IP66/67;	Thread G ½	0.5 kg
				F6	F15 316L Hygiene	IP66/67;	Thread G ½	0.1 kg
				F7	T13 Alu	coated IP66/68; thread G ½		0.9 kg
					Separate connection compartment			
				G1	F27 316L	IP66/68;	M20 threaded joint	
					Ex d > M20 thread			
				G4	F16 Polyester	IP66/67;	M20 threaded joint	
				G5	F13 Alu F17 Alu	IP66/68; IP66/67;	M20 threaded joint	0.5 kg
					Ex d > thread M20			
				G6	F15 316L Hygiene	IP66/67;	M20 threaded joint	0.1 kg
				G7	T13 Alu	coated IP66/68;	M20 threaded joint	0.9 kg
					Separate connection compartment			
				N4	F16 Polyester	IP66/67;	M12 connector	
				N5	F13 Alu F17 Alu	IP66/68; IP66/67;	M12 connector	
				N6	F15 316L hygiene	IP66/67;	M12 connector	
				Y9	Special version			
60					Additional option			
				A	Basic version			
				B	PWIS-free, PWIS = paint-wetting impairment substances, max 2000 mm (78.7 in)			
				C	EN 10204 - 3.1 material (316L wetted) inspection certificate			
				D	EN10204-3.1 AD2000 material, wetted, apart from cast parts, inspection certificate			
				K	Special adjustment, density H20			
				L	Special adjustment, density H20, EN10204-3.1, material (wetted), inspection certificate			
				N	EN 10204 - 3.1 material, NACE MR0175 (316L wetted) Inspection certificate			
				P	100 bar (1450 psi) process pressure			(FTL51)
				R	100 bar (1450 psi) process pressure, EN 10204 - 3.1 material, NACE MR0175 (316L wetted) Inspection certificate			(FTL51)
				S	GL/ABS marine approval for FTL51: ≤ 1600 mm (63 in)			
				Y	Special version			

580									Test, certificate:
									KD Helium leak test, internal procedure, inspection certificate
									KE Pressure test, internal procedure, inspection certificate
									KG PMI test (XRF), internal procedure, wetted metal parts, EN10204-3.1 inspection certificate
									KP Dye penetration test AD2000-HP5-3(PT), wetted/pressurized metal parts, inspection certificate
									KQ Dye penetration test ISO23277-1 (PT), wetted/pressurized metal parts, inspection certificate
									KR Dye penetration test ASME VIII-1 (PT), wetted/pressurized metal parts, inspection certificate
									KS Welding documentation, wetted/pressurized seams
									KV Declaration of Conformity ASME B31.3
									K9 Special version, TSP-No. to be spec.
FTL5x -									Complete product designation



Note!

The basic weight includes the compact sensor, thread adapter G ¾, electronic insert, polyester housing

Liquiphant M FTL50H, FTL51H product structure

Design		Basic weight			
FTL50H	Compact				0.7 kg
FTL51H	With extension pipe				0.7 kg
10	Approval:				
	A	Non-hazardous area			
	B	ATEX II 3G Ex nC IIC T6, WHG, ATEX II 3D Ex tc IIIC T85°C, NEPSI II 3G Ex nC IIC T6			
	C	ATEX II 3G Ex nA IIC T6, WHG, ATEX II 3D Ex tc IIIC T85°C, NEPSI II 3G Ex nA IIC T6			
	D	Non-hazardous area, WHG			
	E	ATEX II 1/2G Ex de IIC T6, WHG			
	F	ATEX II 1/2GD Ex ia IIC T6, WHG/IECEx			
	G	ATEX II 1/2GD Ex ia IIC T6/IECEx Zone0/1			
	H	ATEX II 1G Ex ia IIC T6			
	I	ATEX II 1/2G Ex de IIC T6/IECEx Zone0/1			
	J	ATEX II 1G Ex ia IIC T6, WHG			
	K	ATEX II 1/2G Ex d IIC T6/IECEx Zone0/1			
	L	ATEX II 1/2G Ex d IIC T6, WHG			
	M	NEPSI Ex ia IIC T6			
	N	NEPSI Ex d IIC T6			
	P	FM IS Cl.I,II,III Div.1 Gr.A-G, Zone 0,1,2,20,21,22			
	Q	FM XP Cl.I,II,III Div.1 Gr.B-G, Gr.A-G if E5 housing selected, Zone 1,2			
	R	FM NI Cl.I Div.2 Gr.A-D, Zone 0,1,2,20,21,22			
	S	CSA C/US IS Cl I,II,III Div.1 Gr.A-G, Zone 0,1,2			
	T	CSA C/US XP Cl I,II,III Div.1 Gr.A-G, Zone 1,2			
	U	CSA C/US General Purpose			
	V	TIIS Ex ia IIC T3			
	W	TIIS Ex d IIB T3			
	7	TIIS Ex d IIC T3			
	8	TIIS Ex d IIC T6			
	1	INMETRO Ex ia IIC T6 Ga/Gb			
	2	INMETRO Ex d IIC T6 Ga/Gb			
	3	INMETRO Ex de IIC T6 Ga/Gb			
	Y	Special version, TSP-No. to be spec.			
20	Process connection:				Additional weight
	GQ2	G ¾	316L (FTL50H)	Thread ISO 228	
	Installation > accessories: weld-in adapter				
	GW2*	G 1	316L	Thread ISO 228	0.2 kg
	Installation > accessories: weld-in adapter				
	BA2	DN32 PN6 A	316L	Flange EN 1092-1 (DIN 2527 B)	1.2 kg
	BB2	DN32 PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	2.0 kg
	BC2	DN40 PN6 A	316L	Flange EN 1092-1 (DIN 2527 B)	1.4 kg
	BD2	DN40 PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	2.4 kg
	BE2	DN50 PN6 A	316L	Flange EN 1092-1 (DIN 2527 B)	1.6 kg

20	Process connection:						Additional weight
	BG2	DN50	PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	3.2 kg	
	BH2	DN65	PN6 A	316L	Flange EN 1092-1 (DIN 2527 B)	2.4 kg	
	BK2	DN65	PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	4.3 kg	
	BM2	DN80	PN10/16 A	316L	Flange EN 1092-1 (DIN 2527 B)	4.8 kg	
	BN2	DN80	PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	5.9 kg	
	BO2	DN100	PN10/16 A	316L	Flange EN 1092-1 (DIN 2527 B)	5.6 kg	
	BR2	DN100	PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	7.5 kg	
	B82	DN25	PN25/40 A	316L	Flange EN 1092-1 (DIN 2527 B)	1.4 kg	
	CG2	DN50	PN25/40 B1	316L	Flange EN 1092-1 (DIN 2527 C)	3.2 kg	
	CN2	DN80	PN25/40 B1	316L	Flange EN 1092-1 (DIN 2527 C)	5.9 kg	
	CO2	DN100	PN10/16 B1	316L	Flange EN 1092-1 (DIN 2527 C)	5.6 kg	
	EE2	1" flush-mounted (52001047)		316L		0.3 kg	
	Installation > accessories: weld-in adapter						
	HE2	DN50	Pipe DIN 11850 slotted nut	316L	DIN 11864-1 A	0.3 kg	
	AA2*	1¼"	150 lbs	RF 316/316L	Flange ASME B16.5	1.2 kg	
	AC2*	1½"	150 lbs	RF 316/316L	Flange ASME B16.5	1.5 kg	
	AE2*	2"	150 lbs	RF 316/316L	Flange ASME B16.5	2.4 kg	
	AF2*	2"	300 lbs	RF 316/316L	Flange ASME B16.5	3.2 kg	
	AJ2*	2½"	300 lbs	RF 316/316L (FTL51H)	Flange ASME B16.5	4.8 kg	
	AL2*	3"	150 lbs	RF 316/316L	Flange ASME B16.5	4.9 kg	
	AM2	3"	300 lbs	RF 316/316L (FTL51H)	Flange ASME B16.5	6.8 kg	
	AP2*	4"	150 lbs	RF 316/316L	Flange ASME B16.5	7.0 kg	
	AQ2*	4"	300 lbs	RF 316/316L (FTL51H)	Flange ASME B16.5	11.5 kg	
	A82*	1"	150 lbs	RF 316/316L	Flange ASME B16.5	1.0 kg	
	KA2	10 K 25		RF 316L	Flange JIS B2220		
	KC2	10 K 40		RF 316L	Flange JIS B2220		
	KE2	10 K 50		RF 316L	Flange JIS B2220	1.7 kg	
	KL2	10 K 80		RF 316L	Flange JIS B2220		
	KP2	10 K 100		RF 316L	Flange JIS B2220		
	MA2	DN32	PN25	316L	DIN 11851	0.1 kg	
	MC2	DN40	PN25	316L	DIN 11851	0.2 kg	
	ME2	DN50	PN25	316L	DIN 11851	0.3 kg	
	PE2	DRD	65 mm	316L		0.3 kg	
	TC2*	DN25-38 (1 to 1½")		316L	ISO 2852 Tri-Clamp		
	TE2*	DN40-51 (2")		316L	ISO 2852 Tri-Clamp	0.1 kg	
	TT2	Ingold fitting 25x46mm		316L			
	UE2	SMS 2"	PN25	316L		0.2 kg	
	WE2*	DN65-162 PN10		316L	Varivent N pipe	0.5 kg	
	YY9	Special version					
		* CRN approval					

30	Probe length; Type:					
	FTL50H					
	AC	Compact;	Ra <1.5 µm/59 µin			
	AD	Compact;	Ra <0.3 µm/12 µin			
	AF	Compact;	Ra<0.76 µm/30 µin			
	IC	Compact;	Ra <1.5 µm/59 µin + temperature spacer			0.6 kg
	ID	Compact;	Ra <0.3 µm/12 µin / A3 + temperature spacer			0.6 kg
	QC	Compact;	Ra <1.5 µm/59 µin + pressure-tight feedthrough			0.7 kg
	QD	Compact;	Ra <0.3 µm/12 µin / A3 + pressure-tight feedthrough			0.7 kg
	FTL51H					
	BC mm;	Ra <1.5 µm/59 µin			0.9 kg/m
	BD mm;	Ra <0.3 µm/12 µin / A3			0.9 kg/m
	BFmm;	Ra<0.76 µm/30 µin			0.9 kg/m
	CC inch;	Ra <1.5 µm/59 µin			2.3 kg/100 in
	CD inch;	Ra <0.3 µm/12 µin / A3			2.3 kg/100 in
	cfinch;	Ra<0.76 µm/30 µin			2.3 kg/100 in

30				Probe length; Type:			
			DC	Length: type II*; Ra <1.5 µm/59 µin			0.1 kg
			DD	Length: type II*; Ra <0.3 µm/12 µin / A3			0.1 kg
			JC mm; Ra <1.5 µm/59 µin + Temperature spacer			0.9 kg/m +0.6 kg
			JD mm; Ra <0.3 µm/12 µin + Temperature spacer			0.9 kg/m +0.6 kg
			KC inch; Ra <1.5 µm/59 µin + Temperature spacer			2.3 kg/100 in +0.6 kg
			KD inch; Ra <0.3 µm/12 µin + Temperature spacer			2.3 kg/100 in +0.6 kg
			LC	Length: type II*; Ra <1.5 µm/59 µin + Temperature spacer			0.1 kg +0.6 kg
			LD	Length: type II*; Ra <0.3 µm/12 µin + Temperature spacer,			0.1 kg +0.6 kg
			RC mm; Ra <1.5 µm/59 µin + Pressure-tight feedthrough			0.9 kg/m +0.7 kg
			RD mm; Ra <0.3 µm/12 µin + Pressure-tight feedthrough			0.9 kg/m +0.7 kg
			SC inch; Ra <1.5 µm/59 µin + Pressure-tight feedthrough			2.3 kg/100 in +0.7 kg
			SD inch; Ra <0.3 µm/12 µin + Pressure-tight feedthrough			2.3 kg/100 in +0.7 kg
			TC	Length: type II*; Ra <1.5 µm/59 µin + Pressure-tight feed through,			0.1 kg +0.7 kg
			TD	Length: type II*; Ra <0.3 µm/12 µin + Pressure-tight feed through,			0.1 kg +0.7 kg
			YY	Special version			
			*) Replacing devices: when vertically mounting a Liquiphant M FTL51H with length II, the switch point is at the same height as for a Liquiphant II FTL360, FTL365, FDL30, FDL35. See also Seite 36 "L II" depends on process connection.				
40				Electronics; output:			
			A	FEL50A	PROFIBUS PA		
			D	FEL50D	Density/concentration without WHG approval (Germany)		
			1	FEL51*	2-wire, AC 19 to 253 V		
			2	FEL52*	3-wire PNP, DC 10 to 55 V		
			4	FEL54	Relay DPDT, AC 19 to 253 V, DC 19 to 55 V		
			5	FEL55	8/16 mA, DC 11 to 36 V		
			6	FEL56	NAMUR (L-H signal)		
			7	FEL57	2-wire PFM		
			8	FEL58*	NAMUR + test keys (H-L signal)		
			9	Special version			
			*) Also available in compact housing				
50				Housing; cable entry:			
			C3	Compact 316L	IP66/68;	Cable 5 m	
			D3	Compact 316L	IP65;	Plug Pg11	ISO4400
			E3	Compact 316L Hygiene	NEMA4X;	Plug NPT ½	ISO4400
			N3	Compact 316L Hygiene	IP66/68;	M12 connector	
			E4	F16 Polyester	NEMA4X;	Thread NPT ½	
			E5	F13 Alu F17 Alu	NEMA4X/6P; NEMA4X	Thread NPT ¾	0.5 kg
			E6	F15 316L Hygiene	NEMA4X;	Thread NPT ½	0.1 kg
			E7	T13 Alu	NEMA4X/6P;	Thread NPT ¾	0.9 kg
			Separate connection compartment				
			F4	F16 Polyester	IP66/67;	Thread G ½	
			F5	F13 Alu F17 Alu	IP66/68; IP66/67;	Thread G ½	0.5 kg
			F6	F15 316L hygiene	IP66/67;	Thread G ½	0.1 kg
			F7	T13 Alu	coated IP66/68; thread G ½		0.9 kg
			Separate connection compartment				
			Ex d > M20 thread				
			G4	F16 Polyester	IP66/67;	M20 threaded joint	
			G5	F13 Alu F17 Alu	IP66/68; IP66/67;	M20 threaded joint	0.5 kg
			G6	F15 316L Hygiene	IP66/67;	Ex d > thread M20 M20 threaded joint	0.1 kg
			G7	T13 Alu	coated IP66/68;	M20 threaded joint	0.9 kg

50					Housing; cable entry:
					Separate connection compartment Ex d > thread M20
				N4	F16 Polyester IP66/67; M12 connector
				N5	F13 Alu IP66/68; M12 connector
					F17 Alu IP66/67;
				N6	F15 316L hygiene IP66/67; M12 connector
				Y9	Special version
60					Additional option
				A	Basic version
				B	CoC-ASME BPE, EN10204-3.1 material (316L wetted) Inspection certificate
				C	EN 10204 - 3.1 material (316L wetted), Inspection certificate
				D	EN10204-3.1 AD2000 material, wetted, apart from cast parts, inspection certificate
				K	Special adjustment, density H2O
				L	Special adjustment, density H2O, EN10204-3.1 (316L wetted) inspection certificate
				S	GL/ABS marine approval for FTL51H: ≤ 1600 mm (63 in)
				Y	Special version
FTL5#H -					Complete product designation



Note!

Basic weight = compact sensor, thread adapter G 3/4, electronic insert, stainless steel housing

Accessories















Note!

- All dimensions in mm (in)!
- For additional information on weld-in adapters, refer to TI00426F.
- The tolerance of the thread start between the weld-in adapter and sensor is ± 15°.



Weld-in adapter

Overview

						
	a0008246	a0008251	a0008256	a0011924	a0008248	a0008253
	G³/₄, d=29 (1.14) without flange	G³/₄, d=50 (1.97) with flange	G³/₄, d=55 (2.17) with flange	G1, d=53 (2.09) without flange	G1, d=60 (2.36) with flange	G1 can be positioned
Material roughness μm (μin)	316L 1.5 (59.1)	316L 0.8 (31.5)	316L 0.8 (31.5)	316L 0.8 (31.5)	316L 0.8 (31.5)	316L 0.8 (31.5)
Without inspection certificate EN10204-3.1 material	71258357	71258355	52001052 ³⁾	71258358	52001051 ^{1), 3)}	52001221 ^{2), 3)}
With inspection certificate EN10204-3.1 material	52028295 ³⁾	52018765 ³⁾	52011897 ³⁾	71093129 ^{1), 3)}	52011896 ^{1), 3)}	52011898 ^{2), 3)}
Seal (replacement part: set of 5)	Silicone O-ring 52021717	Silicone O-ring 52021717	Silicone O-ring 52014473	Silicone O-ring 52014472	Silicone O-ring 52014472	Silicone profile gasket 52014424)
Weld-in dummy	–	–	71168889	71166879	71166879	71181945

							
		a0008246	a0008251	a0008256	a0011924	a0008248	a0008253
		G$\frac{3}{4}$, d=29 (1.14) without flange	G$\frac{3}{4}$, d=50 (1.97) with flange	G$\frac{3}{4}$, d=55 (2.17) with flange	G1, d=53 (2.09) without flange	G1, d=60 (2.36) with flange	G1 can be positioned
Liquiphant M	Feature	Version					
FTL50	020			GQ2			
FTL5x					GW2	GW2	GW2
FTL50H				GQ2			
FTL5xH					GW2	GW2	GW2

- 1) This weld-in adapter replaces the weld-in adapter with the order number 917969-1000.
- 2) This weld-in adapter replaces the weld-in adapter with the order number 215159-0000.
- 3) A seal is included in the delivery.

			
		a0008252	a0008254
		RD52	DRD DN50 65 (2.56) (welding flange)
Material		316L	316L/304
roughness μm (μin), process side		0.8 (31.5)	0.8 (31.5)
Without inspection certificate EN10204-3.1 material		52001047 ^{1), 2)}	52002041 ²⁾ / 916743-0000
With inspection certificate EN10204-3.1 material		52006909 ^{1), 2)}	52011899 ²⁾ / –
Seal (replacement part: set of 5)		Silicone profile gasket 52014424	PTFE flat seal 52024228
Weld-in dummy		M40167	–
Device		Feature	Version
Liquiphant M			
FTL5xH		020	EE2
			PE2

- 1) This weld-in adapter replaces the weld-in adapter with the order number 942329-0001.
- 2) A seal is included in the delivery.




Note!

All the weld-in adapters available are described in document TI00426F.

www.endress.com --> Download --> Advanced --> Documentation code --> TI00426F.

Weather protection cover


For F16 housing



A0018225

Material	Order No.	Weight
PBT, gray	71127760	240 g (8.46 oz)

For F13, F17 and F27 housing



A0018226

Material	Order No.	Weight
PA6, gray	71040497	300 g (10.58 oz)


Lap joint flange

Order number: 918158-0000
With G 1 thread for mounting
a Liquiphant FTL50, FTL51
with process connection GR2

Pressure up to 40 bar (580 psi)

Material: corrosion-resistant steel
1.4301 (AISI 304)


Weight: 0.54 kg (1.19 lbs)



L00-FTL5xxxx-06-05-xx-xx-108


Lap joint flanges

- With G 1 thread for mounting a Liquiphant FTL50, FTL51 with process connection GR2
- Material: corrosion-resistant steel 1.4571 (AISI 316Ti)
- Order number: 918143-0000
Flange DN50 PN40, EN 1092-1
Weight: 3.11 kg (6.86 lbs)
 - Order number: 918144-0000
Flange ASME 2", 150 psi, RF
Weight: 2.38 kg (5.25 lbs)



Sliding sleeves for unpressurized operation

- Switch point infinitely variable for Liquiphant M FTL51
- Material: corrosion-resistant steel 1.4435 (AISI 316 L)
- Weight for G 1, NPT 1: 0.21 kg (0.46 lbs)
Weight for G 1½, NPT 1½: 0.54 kg (1.19 lbs)



Thread	Standard	Material	Order number	Approval
G 1	DIN ISO 228/I	1.4435 (AISI 316 L)	52003978	
G 1	DIN ISO 228/I	1.4435 (AISI 316 L)	52011888	With inspection certificate EN 10204 - 3.1 material
NPT1	ASME B 1.20.1	1.4435 (AISI 316 L)	52003979	
NPT1	ASME B 1.20.1	1.4435 (AISI 316 L)	52011889	With inspection certificate EN 10204 - 3.1 material
G 1½	DIN ISO 228/I	1.4435 (AISI 316 L)	52003980	
G 1½	DIN ISO 228/I	1.4435 (AISI 316 L)	52011890	With inspection certificate EN 10204 - 3.1 material
NPT1½	ASME B 1.20.1	1.4435 (AISI 316 L)	52003981	
NPT1½	ASME B 1.20.1	1.4435 (AISI 316 L)	52011891	With inspection certificate EN 10204 - 3.1 material

High pressure sliding sleeves

For continuous adjustment of the switch point of a Liquiphant M FTL51.


Also for use in hazardous areas. For further information → 58ff. (ATEX, NEPSI).

Material: corrosion-resistant steel
1.4435 (AISI 316L) or AlloyC22

Weight for G 1, NPT 1: 1.13 kg (2.49 lbs)


Weight for G 1½, NPT 1½: 1.32 kg (2.91 lbs)

Seal package made of graphite



L00-FTL5xxxx-06-05-xx-xx-110

Thread	Standard	Material	Order number	Approval
G 1	DIN ISO 228/1	1.4435 (AISI 316 L)	52003663	
G 1	DIN ISO 228/1	1.4435 (AISI 316 L)	52011880	With inspection certificate EN 10204 - 3.1 material
G 1	DIN ISO 228/1	AlloyC22	71118691	With inspection certificate EN 10204 - 3.1 material
NPT1	ASME B 1.20.1	1.4435 (AISI 316 L)	52003667	
NPT1	ASME B 1.20.1	1.4435 (AISI 316 L)	52011881	With inspection certificate EN 10204 - 3.1 material
NPT1	ASME B 1.20.1	AlloyC22	71118694	With inspection certificate EN 10204 - 3.1 material
G 1½	DIN ISO 228/1	1.4435 (AISI 316 L)	52003665	
G 1½	DIN ISO 228/1	1.4435 (AISI 316 L)	52011882	With inspection certificate EN 10204 - 3.1 material
G 1½	DIN ISO 228/1	AlloyC22	71118693	With inspection certificate EN 10204 - 3.1 material
NPT1½	ASME B 1.20.1	1.4435 (AISI 316 L)	52003669	
NPT1½	ASME B 1.20.1	1.4435 (AISI 316 L)	52011883	With inspection certificate EN 10204 - 3.1 material
NPT1½	ASME B 1.20.1	AlloyC22	71118695	With inspection certificate EN 10204 - 3.1 material



L00-FTL5xxxx-05-05-xx-xx-002


* FTL51 with high-pressure sliding sleeve (100 bar (1450 psi)). See "Additional option" Seite 43 ff. option "P" or "R".

Cover with sight glass

Order number: 943461-0001
for polyester housing F16

Material: PA 12

Weight: 0.04 kg (0.09 lbs)



L00-FTL5xxxx-03-05-xx-xx-016

Cover with sight glass

For stainless steel housing F15

Material: AISI 316L

Weight: 0.16 kg (0.35 lbs)


– Order number: 52027002

With glass sight glass

– Order number: 52028207

With PC sight glass

(Not for CSA, General Purpose)



L00-FTL5xxxx-03-05-xx-xx-017

Circular connector

Order number: 52010285

4x0.34 M12 socket


Cable: PVC (gray) 5 m (16 ft)

Body: PUR (blue)

Thread adapter nut: Cu Sn/Ni

Degree of protection: IP67

Temperature range: -25 to +70 °C (-13 to +158 °F)



L00-FTL5xxxx-06-05-xx-xx-111

Order number: 52024216

4x0.34 M12 socket


Cable: PVC (orange) 5 m (16 ft)

Body: PVC (orange)

Thread adapter nut: 316L


Degree of protection: IP69K (fully locked)

Temperature range: -25 to +70 °C (-13 to +158 °F)



L00-FTL5xxxx-06-05-xx-xx-112

Order number: 52018763
 4x0.34 M12 socket with integrated LEDs
 Cable: PVC (orange) 5 m (16 ft)
 Body: PVC (transparent)
 Thread adapter nut: 316L
 Degree of protection: IP69K (fully locked)
 Temperature range: -25 to +70 °C (-13 to +158 °F)



Documentation



Note!
 You can find supplementary documentation on the product pages at www.endress.com

Operating Instructions

Electronic insert FEL50A for Liquiphant M, PROFIBUS PA
 BA00141F

Liquiphant M Density, Density Computer FML621
 BA00335F

Liquiphant M FTL50, FTL51
 KA00143F

Liquiphant M FTL50(H), FTL51(H)
 KA00144F

Liquiphant M FTL51C
 KA00162F

Liquiphant M FTL50-##### # 7 #, FTL51-##### # 7 #
 KA00163F

Liquiphant M FTL50H-##### 7 #, FTL51H-##### 7 #
 KA00164F

Liquiphant M FTL51C-##### 7 ##
 KA00165F

Liquiphant M FTL5#-# ### ## # #3 #, FTL5#H-# ### ## # #3 #
 KA00220F

Electronic insert FEL50D for Liquiphant M Density FTL50, FTL51
 KA00284F

Electronic insert FEL50D for Liquiphant M Density FTL50H, FTL51H
 KA00285F

Electronic insert: FEL50D for Liquiphant M Density FTL51C
 KA00286F






Liquiphant M Sliding Sleeve for FTL51, G 1, NPT 1
 KA00151F

Liquiphant M Sliding Sleeve for FTL51, G 1½, NPT 1½
 KA00152F

Liquiphant M High-pressure Sliding Sleeve for FTL51, G 1, NPT 1
 KA00153F

Liquiphant M High-pressure Sliding Sleeve for FTL51, G 1½, NPT 1½
 KA00154F

Technical Information	<p>General instructions for electromagnetic compatibility (Test procedure, installation recommendation) TI00241F</p> <p>Liquiphant M FTL51C, wetted parts with highly corrosion-resistant ECTFE, PFA or enamel coating TI00347F</p> <p>Isolating amplifier FTL325P, 1 or 3-channel switching units for top-hat rail mounting for Liquiphant M with electronic insert FEL57 TI00350F</p> <p>Isolating amplifier FTL325N, 1 or 3-channel switching units for top-hat rail mounting for Liquiphant M with electronic insert FEL56, FEL58 TI00353F</p> <p>Liquiphant S FTL70/71, for medium temperatures up to 280 °C (536 °F) TI00354F</p> <p>Isolating amplifier FTL375P, 1 to 3-channel switching units for top-hat rail mounting for Liquiphant M with electronic insert FEL57 TI00360F</p> <p>Liquiphant M Density, Density Calculator FML621 TI00420F</p> <p>Weld-in adapter, TI00426F</p>
Functional safety (SIL)	<p>Liquiphant M with electronic insert FEL51 (MAX) SD00164F</p> <p>Liquiphant M with electronic insert FEL51 (MIN) SD00185F</p> <p>Liquiphant M with electronic insert FEL52 (MAX) SD00163F</p> <p>Liquiphant M with electronic insert FEL52 (MIN) SD00186F</p> <p>Liquiphant M with electronic insert FEL54 (MAX) SD00162F</p> <p>Liquiphant M with electronic insert FEL54 (MIN) SD00187F</p> <p>Liquiphant M with electronic insert FEL55 (MAX) SD00167F</p> <p>Liquiphant M with electronic insert FEL55 (MIN) SD00279F</p> <p>Liquiphant M with electronic insert FEL57 + Nivotester FTL325P (MAX) SD00111F</p> <p>Liquiphant M with electronic insert FEL57 + Nivotester FTL325P (MIN) SD00231F</p> <p>Liquiphant M with electronic insert FEL57+ Nivotester FTL375P (MAX) SD00113F</p> <p>Liquiphant M with electronic insert FEL56 + Nivotester FTL325N (MAX) SD00168F</p> <p>Liquiphant M with electronic insert FEL56 + Nivotester FTL325N (MIN) SD00188F</p> <p>Liquiphant M with electronic insert FEL58 + Nivotester FTL325N (MAX) SD00161F</p> <p>Liquiphant M with electronic insert FEL58 + Nivotester FTL325N (MIN) SD00170F</p>

Safety Instructions (ATEX)	<p> CE  II 1/2 G, Ex d IIC/B (KEMA 99 ATEX 1157) XA00031F/00/a3 </p> <p> CE  II 1/2 G, Ex ia/ib IIC/B (KEMA 99 ATEX 0523) XA00063F/00/a3 </p> <p> CE  II 1 G, Ex ia IIC/B (KEMA 99 ATEX 5172 X) XA00064F/00/a3 </p> <p> CE  II 1/2 G, Ex de IIC/B (KEMA 00 ATEX 2035) XA00108F/00/a3 </p> <p> CE  II 3 G, Ex nA/nC II (EG 01 007-a) XA00182F/00/a3 </p>
Safety Instructions (NEPSI)	<p> Ex d IIC/IIB T3-T6, Ex d IIC T2-T6 (NEPSI GYJ06424) XA00401F/00/B2 </p> <p> Ex ia IIC T2-T6, Ex ia IIB T3-T6 (NEPSI GYJ05556, NEPSI GYJ06464), XC00009F/00/b2 </p> <p> Ex nA II T3-T6, Ex nC/nL IIC T3-T6 (NEPSI GYJ04360, NEPSI GYJ071414) XC00010F/00/b2 </p>
Control Drawings	<p> Liquiphant M (IS and NI) Current output PFM, NAMUR Entity installation Class I, Div. 1, 2, Groups A, B, C, D Class I, Zone 0 Class II, Div. 1, 2, Groups E, F, G Class III ZD00041F </p> <p> Liquiphant M, Liquiphant S (cCSAus / IS) Class I, Div. 1, Groups A, B, C, D Ex ia IIC T6 Class II, Div. 1, Groups E, F, G Class III ZD00042F </p> <p> Liquiphant M (NI), FTL50(H), FTL51(H), FTL51C, FTL70, FTL71 Class I, Div. 2, Groups A, B, C, D Class II, Div. 2, Groups F, G Class III ZD00043F </p> <p> Liquiphant M, Liquiphant S (cCSAus / XP) Class I, Groups A, B, C, D Class II, Groups E, F, G Class III ZD00240F </p> <p> Liquiphant M (IS and NI) PROFIBUS PA, FOUNDATION Fieldbus Class I, Zone 0, IIC Class I, Division 1, 2, Groups A, B, C, D Class II, Division 1, 2, Groups E, F, G Class III ZD00244F </p>
System information	<p> Liquiphant M SI00040F </p>



www.addresses.endress.com
