

# TES-1260 Humidity Temperature Meter



## FEATURES

Dual LCD display.  
Dew Point Reading.  
Wet bulb Reading.  
MAX/MIN with Time Stamp.  
Data Hold function.  
°C & °F Switchable.  
DATA memory and read function  
(99 readings from LCD display)  
Auto Power Off.



## SPECIFICATION

<b>Measuring Range</b>	<b>Temperature</b> : -20°C ~ 60°C (-4°F ~ 140°F) <b>Humidity</b> : 1%RH ~ 99%RH
<b>Resolution</b>	0.1°C / 0.1°F / 0.1%RH
<b>Accuracy</b>	<b>Temperature</b> : ±0.5°C, ±0.9°F <b>Humidity</b> : ±3%RH (at 25°C, 30 ~ 99%RH) ±5%RH (at 25°C, 1 ~ 30%RH)
<b>Data Memory Capacity</b>	Manual recording : 99 data sets (Direct reading from LCD display.)
<b>Sampling Rate</b>	2 times/sec
<b>Operating Conditions</b>	0°C ~ 60°C (32°F ~ 140°F) below 99% R.H. (no condensation)
<b>Power Source</b>	9V Battery
<b>Battery Life</b>	Approx. 200 hours
<b>Size &amp; Weight</b>	193mm(L) × 59mm(W) × 26mm(H) / 140g
<b>Accessories</b>	Instruction manual, Battery.