



Level



Pressure



Flow



Temperature

Liquid
Analysis

Registration

Systems
Components

Services



Solutions

Technical Information

Liquicap M FMI51, FMI52

Capacitance level measurement

For continuous measurement in liquids



Application

The Liquicap M FMI5x compact transmitter is used for the continuous level measurement of liquids.

Thanks to its robust and tried-and-tested construction, the probe can be used both in vacuums and in overpressure up to 100 bar. The materials used allow operating temperatures in the medium container of $-80\text{ }^{\circ}\text{C}$ to $+200\text{ }^{\circ}\text{C}$.

Used in conjunction with Fieldgate (remote measured value interrogation via the Internet), Liquicap M provides an ideal solution for inventorying materials and optimizing logistics (inventory control).

Your benefits

- No calibration necessary for media with a conductivity of $100\text{ }\mu\text{S}/\text{cm}$ and higher. The probes are calibrated to the ordered probe length on leaving the factory (0 % to 100 %). This makes easy and fast commissioning possible.
- Menu-guided local configuration via plain text display (optional)
- Universal application thanks to wide range of certificates and approvals
- Use also in safety systems requiring functional safety to SIL2 in accordance with IEC 61508
- Corrosion-resistant, FDA-listed materials in contact with the process
- Can be switched for media forming buildup
- Short reaction times
- No need for recalibration after replacing electronics
- Automatic monitoring of electronics and possible damage to insulation, as well as rod breaking or rope tearing
- Suitable for interface measurement

Table of contents

Function and system design	3
Measuring principle	3
Measuring system	4
System integration via Fieldgate	6
Operating conditions: Installation	7
Installation instructions	7
With separate housing	8
Operating conditions: Environment	9
Ambient temperature range	9
Storage temperature	9
Climate class	9
Vibration resistance	9
Shock resistance	9
Cleaning	9
Degree of protection	10
Electromagnetic compatibility (EMC)	10
Operating conditions: Process	11
Process temperature range	11
Process pressure limits	12
Pressure and temperature derating	12
Liquicap M operational range	14
Mechanical construction	15
Weight	22
Technical data: probe	22
Material	22
Input	23
Measured variable	23
Measuring range	23
Measuring condition	23
Output	24
Output signal	24
Signal on alarm	24
Linearization	24
Power supply	25
Electrical connection	25
Connector	25
Terminal assignment	25
Supply voltage	26
Cable entry	26
Power consumption	26
Current consumption	26
Performance characteristics	27
Reference operating conditions	27
Maximum measured error	27
Influence of ambient temperature	27
Switch-on behavior	27
Measured value reaction time	27
Integration time	27

Accuracy of factory calibration	27
Resolution	28
Human interface	29
Electronic inserts	29
Local operation with display	29
Remote operation with handheld terminal	30
Remote operation via FieldCare Device Setup	31
Certificates and approvals	32
CE mark	32
Ex approval	32
Other standards and guidelines	32
Additional approvals	32
Ordering information	33
Liquicap M FMI51	33
Liquicap M FMI52	37
Accessories	40
Protective cover	40
Shortening kit for FMI52	40
Commubox FXA191, FXA195 HART	40
Overvoltage protection HAW56x	40
Weld-in adapter	40
Spare Parts	40
Documentation	41
Technical Information	41
Operating Instructions	41
Certificates	41
Patents	42

Function and system design

Measuring principle


The principle of capacitance level measurement is based on the change in capacitance of the capacitor due to the change in the level. The probe and container wall (conductive material) form an electric capacitor. When the probe is in air ①, a certain low initial capacitance is measured.

When the container is filled, the capacitance of the capacitor increases the more the probe is covered ②, ③. As a conductivity of 100 $\mu\text{S}/\text{cm}$, the measurement is independent of the value for the dielectric constant (DK) of the liquid. As a result, fluctuations in the DK value do not affect the measured value display. Furthermore, the system also prevents the effect of medium buildup or condensate near the process connection for probes with an inactive length.



Note!

A ground tube is used as a counterelectrode for containers made of nonconductive materials.



100-FMI5xxxx-15-05-xx-xx-001

R : Conductivity of the liquid

C : Capacitance of the liquid

C_A : Initial capacitance (probe not covered)

C_E : Final capacitance (probe covered)

ΔC : Change in capacitance

Function

The selected electronic insert of the probe (e.g. FEI50H 4 to 20 mA HART) converts the measured change in capacitance of the liquid to a signal that is proportional to the level.

Phase-selective measurement

The evaluation of the container capacitance works along the principle of phase-selective measurement. In this process, the amount of alternating current and the phase shift between the voltage and current is measured. With these two characteristic quantities, the capacitance idle current can be calculated by the medium capacitor and the real current by the medium resistance. Conductive buildup stuck to the probe rod/rope acts like additional medium resistance and causes an error in measurement. As the size of the medium resistance can be determined with phase-selective measurement, the system compensates for the buildup on the probe.

Interface measurement

A prior adjustment also ensures a certain and definite measured value even if the emulsion layer is of varying thickness. It is always the average value of the emulsion film measured.

The calibration values for empty and full calibration can be calculated with the FieldCare operating program from Endress+Hauser.



L00-FMI5xxxx-15-05-xx-xx-000

1.) Water, for example (the medium must be conductive $\geq 100 \mu\text{S}/\text{cm}$)

2.) Emulsion

3.) Oil, for example (nonconductive medium $< 1 \mu\text{S}/\text{cm}$)

Measuring system

PFM output (FEI57C)


The complete measuring system consists of:

- The capacitance Liquicap M FMI51 or FMI52 level probe
- The FEI57C electronic insert
- A transmitter power supply unit



Note!

- The twin-core feeder is also used for PFM signal transmission.
- In combination with a power supply unit the FEC57C will only run in a 1-channel-mode and without an automatic alignment correction.



L00-FMI5xxxx-14-00-06-xx-001

Level measurement

4 to 20 mA output with HART protocol (FEI50H)


The complete measuring system consists of:

- The capacitance Liquicap M FMI51 or FMI52 level probe
- The FEI50H electronic insert
- A transmitter power supply unit (e.g. RN221N, RNS221, RMA421, RMA422)



Note!

DC voltage must be supplied to the electronic insert. The twin-core feeder is also used for HART protocol signal transmission.



Local operation

- Standard - via keys and switches on the electronic insert
- Optional - via display and operating module

Remote operation

- With HART handheld terminal DXR375/475
- With a personal computer, Commubox FXA195 and the operating program FieldCare.



Note!

FieldCare is a graphic operating program and is used to support commissioning, data backup, signal analysis and documentation of the measuring point.


System integration via Fieldgate

Vendor managed inventory

The remote interrogation of tank or silo levels via Fieldgate enables suppliers of raw materials to gather information about the current inventories of their regular customers at any time and, for example, take this into account in their own production planning. The Fieldgate monitors the configured level limits and automatically triggers the next order as required. Here, the range of possibilities ranges from simple requisitioning by e-mail through to fully automatic order processing by incorporating XML data into the planning systems on both sides.

Remote maintenance of measuring systems

Not only does Fieldgate transmit the current measured values, it also alerts the standby personnel responsible by e-mail or SMS as required. Service technicians can diagnose and configure the connected HART devices remotely in the event of an alarm or also for routine checks. All that is required for this is the appropriate HART operating software (e.g. FieldCare) for the connected device. Fieldgate forwards the information transparently. In this way, all options of the operating software in question are available remotely. By using remote diagnosis and remote configuration some onsite service operations can be avoided and all others can at least be planned and prepared better.



Operating conditions: Installation

Installation instructions




Liquicap M FMI51 (rod probe) can be installed vertically from above or below.
Liquicap M FMI52 (rope probe) can be installed vertically from above.

Note!


- The probe may not come into contact with the container wall! Do not install probes in the area of the filling curtain!
- When using in agitating tanks, make sure you install at a safe distance from the agitator.
- Rod probes with a ground tube should be used in the event of severe lateral load.
- When mounting, ensure there is a good electrically conductive connection between the process connection and the tank. Use an electrically conductive sealing band for example.

For containers that conduct electricity e.g. steel tanks



L00-FMI5xxxx-11-06-xx-xx-001

For containers that do not conduct electricity e.g. plastic tanks



L00-FMI5xxxx-11-06-xx-xx-002


Probe with ground tube and grounding

With separate housing



Note!

- The maximum connection length between the probe and the separate housing is 6 m (L4). The desired length must be quoted when ordering a Liquicap M with a separate housing.
- The overall length $L = L1 + L4$ may not exceed 10 m.
- If the connecting cable is to be shortened or passed through a wall, it must be separated from the process connection.
- For information on ordering, please refer also to the "Ordering information" => "Probe design" on → 33.



Rod length L1 max. 4 m


Rope length L1 max. 9.7 m (the maximum total length of L1 + L4 should not exceed 10 m).

Extension heights

Housing side: wall mounting

Housing side: pipe mounting

Sensor side



Note!

- The cable has a bending radius of $r \geq 100$ mm
- Connecting cable: $\varnothing 10.5$ mm
- Outer jacket: silicone, notch-resistant

	Polyester housing (F16)	Stainless steel housing (F15)	Aluminum housing (F17)
B (mm)	76	64	65
H1 (mm)	172	166	177


		H5 (mm)	D (mm)
Probes Ø10 mm rod		66	38
Probes Ø16 mm rod or rope (without fully insulated inactive length)	G¾", G1", NPT¾", NPT1", Clamp 1", Clamp 1½", Universal Ø44, flange <DN 50, ANSI 2", 10K50	66	38
	G1½", NPT1½", Clamp 2", DIN 11851, flanges ≥DN 50, ANSI 2", 10K50	89	50
Probes Ø 22 mm rod or rope (with fully insulated inactive length)		89	38

Wall holder unit



Note!

- The wall holder unit is part of the scope of supply for device versions with a separate housing.
- The wall holder unit first has to be screwed to the separate housing before you can use it as a drilling template. The distance between the holes is reduced by screwing it to the separate housing.



L00-FMI5xxxx-06-05-xx-xx-065

Operating conditions: Environment

Ambient temperature range

- -50 to +70 °C
- -40 to +70 °C (with F16 housing)
- Observe derating → 11
- If operating outdoors, use a protective cover! → 40.

Storage temperature

-50 to +85 °C

Climate class

DIN EN 60068-2-38/IEC 68-2-38: test Z/AD

Vibration resistance

DIN EN 60068-2-64/IEC 68-2-64: 20 Hz– 2000 Hz; 0.01 g²/Hz

Shock resistance

DIN EN 60068-2-27/IEC 68-2-27: 30g acceleration

Cleaning

Housing:

When cleaning, make sure that the cleaning agent used does not attack or corrode the housing surface or seals.

Probe:

Depending on the application, buildup (contamination and soiling) can form on the probe rod. A high degree of material buildup can affect the measurement result. If the medium tends to create a high degree of buildup, regular cleaning is recommended. When cleaning, it is important to make sure that the insulation of the probe rod is not damaged.

Degree of protection

	IP66*	IP67*	IP68*	NEMA4X**
Polyester housing F16	X	X	–	X
Stainless steel housing F15	X	X	–	X
Aluminum housing F17	X	X	–	X
Aluminum housing F13 with gas-tight process seal	X	–	X***	X
Stainless steel housing F27 with gas-tight process seal	X	X	X***	X
Aluminum housing T13 with gas-tight process seal and separate connection compartment (Ex d)	X	–	X***	X
Separate housing	X	–	X***	X

*as per EN60529

** as per NEMA 250

*** Only with M20 cable entry or G1/2 thread

Electromagnetic compatibility (EMC)

- Interference emission to EN 61326, Electrical Equipment Class B
Interference immunity to EN 61326, Annex A (Industrial) and NAMUR Recommendation NE 21 (EMC)
Failure current acc. Namur NE43: FEI50H = 22mA
- A usual commercial instrument cable can be used.

Operating conditions: Process

Process temperature range

The following diagrams apply for:


- Rod and rope version
- Insulation: PTFE, PFA, FEP
- Standard applications outside hazardous areas



Note!

The temperature is restricted to $T_a -40\text{ °C}$ if the polyester housing F16 is used or if additional option B is selected (free from paint-wetting impairment substances, only FMI51).

With compact housing




L00-FMI5xxxx-05-05-xx-xx-013

T_a : Ambient temperature

T_p : Process temperature

With separate housing



L00-FMI5xxxx-05-05-xx-xx-011

T_a = Ambient temperature

T_p = Process temperature

* The permitted ambient temperature at the separate housing is the same as indicated for the compact housing.

Process pressure limits
Probe ø10 mm (including insulation)

–1 to 25 bar (observe dependencies: process temperature and process connection → 11 and → 17).

Probe ø16 mm (including insulation)

- –1 to 100 bar (observe dependencies: process temperature and process connection → 11 and → 17).
- In the event of an inactive length, the maximum permitted process pressure is 63 bar
- In the event of CRN approval and inactive length, the maximum permitted process pressure is 32 bar.

Probe ø22 mm (including insulation)

–1 to 50 bar (observe dependencies: process temperature and process connection → 11 and → 17).

Refer to the following standards for the pressure values permitted at higher temperatures:

- EN 1092-1: 2005 Table, Appendix G2
With regard to its resistance/temperature property, the material 1.4435 is identical to 1.4404 (AISI 316L) which is grouped under 13E0 in EN 1092-1 Tab. 18. The chemical composition of the two materials can be identical.
- ASME B 16.5a - 1998 Tab. 2-2.2 F316
- ASME B 16.5a - 1998 Tab. 2.3.8 N10276
- JIS B2238/2210

In each case it applies to the lowest value from the derating curves of the device and the selected flange.

Pressure and temperature derating

For process connections ½", ¾", 1", flanges < DN50, < ANSI 2", < JIS 10K (10 mm rod)

For process connections ¾", 1", flanges < DN50, < ANSI 2", < JIS 10K (16 mm rod)


Rod insulation: PTFE, PFA

Rope insulation: FEP, PFA



Note!

See also "Process connections" → 17.



L00-FMI5xxxx-05-xx-xx-008

P_p : Process pressure

T_p : Process temperature

For process connections 1½", flanges ≥ DN50, ≥ ANSI 2", ≥ JIS 10K (16 mm rod)


Rod insulation: PTFE, PFA

Rope insulation: FEP, PFA



Note!

See also "Process connections" → 17




P_p : Process pressure

T_p : Process temperature


* For probes with an inactive length .

With a fully insulated inactive length (22 mm rod):



P_p : Process pressure

T_p : Process temperature

Liquicap M operational range

L00-FMI5xxxx-05-06-xx-en-000

Typical DC values (dielectric constant)

Air	1
Vacuum	1
General liquefied gases	1.2 - 1.7
Gasoline	1.9
Cyclohexane	2
Diesel fuel	2.1
General oils	2 - 4
Methyl ether	5
Butanol	11
Ammonia	21
Latex	24
Ethanol	25
Caustic soda	22 - 26
Acetone	20
Glycerine	37
Water	81

**Note!**


Further DC-values are available in file "CP00019F" on:

www.endress.com => Download => Advanced => Documentation code = CP00019F => Start search

Mechanical construction



Note!
All dimensions in mm.




L00-FMI5xxxx-03-05-xx-en-001

Housing




Note!
High cover for display (optional).

Polyester housing F16




L00-FMI5xxxx-06-05-xx-en-001

Stainless steel housing F15



L00-FMI5xxxx-06-05-xx-en-003


Aluminum housing F17



L00-FMI5xxxx-06-05-xx-en-002


Aluminum housing F13 With gas-tight process seal

Stainless steel housing F27 with gas-tight process seal









L00-FMI5xxxx-06-05-xx-en-000

Aluminum housing T13 With separate connection compartment and gas-tight process seal








L00-FMI5xxxx-06-05-xx-en-004

Extension height of housing with adapter

	Polyester housing F16	Stainless steel housing F15	Aluminum housing F17	Aluminum housing F13	Aluminum housing F27	Aluminum housing T13
	 L00-FMI5xxxx-06-05-xx-xx-044	 L00-FMI5xxxx-06-05-xx-xx-046	 L00-FMI5xxxx-06-05-xx-xx-045	 L00-FMI5xxxx-06-05-xx-xx-048	 L00-FMI5xxxx-06-05-xx-xx-048	 L00-FMI5xxxx-06-05-xx-xx-047
Order code	2	1	3	4	4	5
H1 (without display)	143	141	150	194	194	210
H2 (with display)	162	179	179	223	223	223

Process connections

	Thread G		Thread NPT		Threaded pipe joint	Tri-Clamp		Tri-Clamp clad	
	 L00-FMI5xxxx-06-05-xx-en-007 (DIN EN ISO 228-1)		 L00-FMI5xxxx-06-05-xx-en-008 (ANSI B 1.20.1)		 L00-FMI5xxxx-06-05-xx-xx-040 (DIN11851)	 L00-FMI5xxxx-06-05-xx-xx-041 (ISO2852)	 L00-FMI5xxxx-06-05-xx-xx-103 (ISO2852)		
Rod probes Ø 10, rope probes									
For pressures up to	25 bar		25 bar		25 bar	25 bar**		—	
Version / order code	G ½ / GCJ G ¾ / GDJ G 1 / GEJ		NPT ½ / RCJ NPT ¾ / RDJ NPT 1 / REJ		DN50 PN40 / MRJ	DN25 (1") / TCJ DN38 (1½") / TJJ		—	
Dimensions	H3 = 38 H4 = 19 AF = 41		H3 = 38 H4 = 19 AF = 41		H3 = 57	H3 = 57		—	
Surface roughness***	—		—		≤ 0.8 µm	≤ 0.8 µm		—	
Additional information	Elastomer flat seal		—		—	EHEDG*, 3A*		—	
Rod probes Ø16, rope probes									
For pressures up to	25 bar	100 bar	25 bar	100 bar	40 bar	25 bar**	40 bar**	16 bar**	16 bar**
Version / order code	G ¾ / GDJ G 1 / GEJ	G 1½ / GGJ	NPT ¾ / RDJ NPT 1 / REJ	NPT 1½/ RGJ	DN50 PN40 / MRJ	DN38 / TNJ (1½")	DN40-51 / TDJ (2")	DN38 / TJK (1½")	DN40-51 TDK (2")
Dimensions	H3 = 38 H4 = 19 AF = 41	H3 = 41 H4 = 25 AF = 55	H3 = 38 H4 = 19 AF = 41	H3 = 41 H4 = 25 AF = 55	H3 = 66	H3 = 98****	H3 = 66	H2 = 66	
Surface roughness***	—		—		≤ 0.8 µm	≤ 0.8 µm		≤ 0.8 µm	
Additional information	Elastomer flat seal		—		—	EHEDG*, 3A*		EHEDG, 3A*	
Rod probes Ø 22, rope probes									
For pressures up to	50 bar		50 bar		—	—			
Version / order code	G1½ / GGJ		NPT1½ / RGJ		—	—			





	Thread G	Thread NPT	Threaded pipe joint	Tri-Clamp	Tri-Clamp clad	
Dimensions	H3 = 85 H4 = 25 AF = 55	H3 = 85 H4 = 25 AF = 55	–	–		
Additional information	Elastomer flat seal	–	–	–		

* EHEDG, 3A: Certificate only applies for probes without an inactive length and with a fully insulated probe rod.

** In the event of CRN approval, the maximum permitted process pressure is 11 bar.

*** Not in conjunction with inactive length.

**** Process connection: Tri-Clamp (47 mm) with detachable clamp (49 mm) and seal (2 mm).

	Flanges	Hygiene connection	Hygiene connection	Hygiene connection
	 (EN1092-1) (ANSI B 16.5) (JIS B2220)	 Thread with flush-mounted seal	 Thread with flush-mounted seal	 Adapter 44 mm with flush-mounted seal
Rod probes Ø10, rope probes				
For pressures up to	Max. 25 bar (depends on flange)	25 bar	25 bar	–
Version / order code	EN / B## ANSI / A## JIS / K##	G¾ / GQJ	G1 / GWJ	–
Dimensions	H3 = 57	H3 = 31 H4 = 26 AF = 41	H3 = 30 H4 = 27 AF = 41	–
Additional information	Also clad (PTFE)	Weld-in adapter see "Accessories"Seite 40 EHEDG*, 3A*	Weld-in adapter see "Accessories"Seite 40 EHEDG*, 3A*	–
Rod probes Ø16, rope probes				
For pressures up to	Max. 100 bar (depends on flange)	–	–	16 bar (tightening torque 10 Nm)
Version / order code	EN / B## ANSI / A## JIS / K##	–	–	Universal adapter / UPJ
Dimensions	H3 = 66	–	–	H3 = 57
Additional information	Also clad (PTFE)	–	–	Universal adapter see "Accessories"°
Rod probes Ø22, rope probes				
For pressures up to	Max. 50 bar (depends on flange)	–	–	–
Version / order code	EN / B## ANSI / A## JIS / K##	–	–	–
Dimensions	H3 = 111	–	–	–
Additional information	Only clad (PTFE)	–	–	–

* EHEDG, 3A: Certificate only applies for probes without an inactive length and with a fully insulated probe rod.

Rod probes FMI51



Note!

- The active probe rod is always fully insulated (dimension L1).
- Total length of probe from sealing surface: $L = L1 + L3$
- Thickness of insulation for probe rod \varnothing 10 mm = 1 mm; 16 mm = 2 mm; 22 mm = 2 mm
- For conductive liquids ($>100 \mu\text{S}/\text{cm}$), the probe is calibrated at the factory to the probe length ordered (0 % to 100 %). For nonconductive liquids ($<1 \mu\text{S}/\text{cm}$), 0% calibration is performed at the factory. The 100% calibration has to be carried out on site.
- The insulation is welded approx. 10 mm at the tip of the probe. This range is not part of the active measuring range.
- Length tolerances L1, L3: < 1 m: 0 to -5 mm, 1 to 3 m: 0 to -10 mm, 3 to 6 m: 0 to -20 mm

	Rod probe		Rod probe with ground tube		Rod probe with inactive length		Rod probe with inactive length and ground tube		Rod probe with fully insulated inactive length
<p>100-FMI5xxxx-06-05-xx-xx-102</p>									<p>L00-FMI5xxxx-06-05-xx-xx-051</p>
Total length (L)	100...4000		100...4000		200...6000		200...6000		300...4000
Active rod length (L1)	100...4000		100...4000		100...4000		100...4000		150...3000
Inactive rod length (L3)	—		—		100...2000		100...2000		150...1000
Ø Probe rod	10	16	10	16	10	16	10	16	22**
Ø Ground tube with or without inactive length	—	—	22	43	22	43	22	43	22**
Lateral loading capacity (Nm) at 20 °C	< 15	< 30	< 40	< 300	< 30	< 60	< 40	< 300	< 25
For use in agitating tanks	—		—	X	—		—	X	—
For conductive liquids $> 100 \mu\text{S}/\text{cm}$	X		—		X		—		X
For nonconductive liquids $< 1 \mu\text{S}/\text{cm}$	—		X		—		X		—
For aggressive liquids	X		—		—		—		X
For high-viscosity liquids	X		—		X		—		X
For use in plastic tanks	—		X		—		X		—
For use in mounting nozzles	—		—		X		X		X
In the event of condensate on tank ceiling	—		—		X		X		X

* H4 = Thread height (important for calculating the exact probe length for process connections with a thread.) → 17

** Probe tube

Rod probes FMI51 for hygiene applications

Note!

- Total length of probe from sealing surface: $L = L1$
- Thickness of insulation with probe rod diameter 16 mm = 2 mm
- In the case of high-viscosity, conductive media that tend to form buildup, always use a fully insulated probe with active buildup compensation.
- Length tolerances L1: <1 m: 0 to -5 mm, 1 to 3 m: 0 to -10 mm, 3 to 6 m: 0 to -20 mm

	Rod probe with clad Tri-Clamp
Total length (L)	100...4000
Active rod length (L1)	100...4000
Probe rod diameter	16
Ø Ground tube	—
Ø Inactive length	—
Ø Active buildup compensation	—
Length, active buildup compensation	—
Lateral loading capacity (Nm) at 20 °C	< 30
For use in agitating tanks	—
For conductive liquids > 100 µS/cm	X
For high-viscosity conductive liquids	—
For nonconductive liquids < 1 µS/cm	X
For aggressive liquids	X
For high-viscosity liquids	X
For use in plastic tanks	—
For use in mounting nozzles	—
In the event of condensate on tank ceiling	—


FMI52 rope probes**Note!**

- The active probe length is always fully insulated (dimension L1).
- Total length of probe from sealing surface: $L = L1 + L3$
- All rope probes are prepared for tensioning in containers (tensioning weight / anchor hole)
- For conductive liquids ($>100 \mu\text{S}/\text{cm}$), the probe is calibrated at the factory to the probe length ordered (0 % to 100 %). For nonconductive liquids ($< 1 \mu\text{S}/\text{cm}$) 0% calibration is performed at the factory. Only the 100% calibration has to be carried out on site.
- Not suitable for agitator tanks, high-viscosity liquids and plastic tanks.
- Thickness of rope insulation 0.75 mm
- In the range of the anchor weight the measurement is not linear.
- Length tolerances L1, L3: <1 m: 0 to -10 mm, 1 to 3 m: 0 to -20 mm, 3 to 6 m: 0 to -30 mm, 6 to 12 m: 0 to -40 mm

	Rope probe	Rope probe with clad Tri-Clamp	Rope probe with inactive length (uninsulated)	Rope probe with fully insulated inactive length
<p>L00-FMI5xxxx-06-05-xx-xx-070</p>				<p>L00-FMI5xxxx-06-05-xx-xx-036</p>
Total length (L)	420...10000		570...10000	570...10000
Active rope length (L1)	420...10000		420...9850	420...9850
Inactive length (L3)	—		150...2000	150...1000
Ø Inactive length	—		22/43*	22**
Ø Probe rope	4		4	4
Ø Anchor weight	22		22	22
Ø Anchor hole	5		5	5
Tensile loading capacity (N) of probe rope at 20 °C	200		200	200
For aggressive liquids	X		—	X
For use in mounting nozzles	—		X	X
For conductive liquids $> 100 \mu\text{S}/\text{cm}$	X		X	X
For aggressive liquids	X		—	X
For high-viscosity liquids	—		—	—
For nonconductive liquids $< 1 \mu\text{S}/\text{cm}$	—		X	X
In the event of condensate on tank ceiling	—		X	X

* The Ø value of the inactive length depends on the process connection selected → 33 ff.


** Probe tube

Weight	<p>Housing with process connection:</p> <ul style="list-style-type: none"> ■ F15, F16, F17, F13 approx. 4.0 kg ■ T13 approx. 4.5 kg ■ F27 approx. 5.5 kg <p>+ Flange weight</p> <p>+ Probe rod Ø 10 mm: 0.5 kg/m,</p> <p>+ Probe rod Ø 22 mm: 0.8 kg/m</p> <p>+ Probe rod Ø 16 mm: 1.1 kg/m</p> <p>+ Probe rope: 0.04 kg/m</p>
Technical data: probe	<p>Capacitance values of probe</p> <ul style="list-style-type: none"> ■ Basic capacitance: approx. 18 pF <p>Additional capacitance</p> <ul style="list-style-type: none"> ■ Mount the probe with a minimum distance of 50 mm from a conductive container wall: <ul style="list-style-type: none"> Probe rod: approx. 1.3 pF/100 mm in air Probe rope: approx. 1.0 pF/100 mm in air ■ Fully insulated probe rod in water: <ul style="list-style-type: none"> Approx. 38 pF/100 mm (16 mm rod) Approx. 45 pF/100 mm (10 mm rod) Approx. 50 pF/100 mm (22 mm rod) ■ Insulated probe rope in water: approx. 19 pF/100 mm ■ Rod probe with ground tube: <ul style="list-style-type: none"> – Insulated probe rod: in air approx. 6.4 pF/100 mm – Insulated probe rod: in water approx. 38 pF/100 mm (16 mm rod) – Insulated probe rod: in water approx. 45 pF/100 mm (10 mm rod) <p>Probe lengths for continuous measurement in conductive liquids</p> <ul style="list-style-type: none"> ■ Rod probe (range 0 to 2000 pF for ≤ 4000 mm) ■ Rope probe < 6 m (range 0 to 2000 pF) ■ Rope probe > 6 m (range 0 to 4000 pF)
Material	<p>Material specifications as per AISI and DIN-EN.</p> <p>In contact with the process</p> <ul style="list-style-type: none"> ■ Probe rod, ground tube, inactive length, tensioning weight for rope probe: 316L (1.4435) ■ Probe rope: 316 (1.4401) ■ Probe rod insulation: PFA or PTFE (FDA 21 CFR 177.1550) ■ Probe rope insulation: PFA or FEP (FDA 21 CFR 177.1550) ■ Process connection: 316L (1.4435 or 1.4404) ■ Flat seal for process connection G ¾ or G 1: elastomer fiber, asbestos-free ■ Sealing ring for process connection G ½, G ¾, G 1, G 1½: Elastomer fiber, asbestos-free, resistant to lubricants, solvents, steam, weak acids and alkalis; to 300 °C and to 100 bar <p>Not in contact with the process</p> <ul style="list-style-type: none"> ■ Ground terminals on housing (exterior): 304 (1.4301) ■ Nameplate on housing (exterior): 304 (1.4301) ■ Cable glands <ul style="list-style-type: none"> – Housing F13, F15, F16, F17, F27: polyamide (PA) With C, D, E, F, H, M, J, P, S, 1, 4, 5 approval (→  33 ordering information): nickel-plated brass – Housing T13: nickel-plated brass ■ Polyester housing F16: PBT-FR with cover made of PBT-FR or with sight glass made of PA12, <ul style="list-style-type: none"> – Cover seal: EPDM – Adhesive nameplate: polyester foil (PET) – Pressure compensation filter: PBT-GF20 ■ Stainless steel housing F15: 316L (1.4404) <ul style="list-style-type: none"> – Cover seal: silicone – Cover clamp: 304 (1.4301) – Pressure compensation filter: PBT-GF20, PA ■ Aluminum housing F17/F13/T13: EN-AC-ALSi10Mg, plastic-coated, <ul style="list-style-type: none"> – Cover seal: EPDM

- Cover clamp: nickel-plated brass
- Pressure compensation filter: silicone (not T13)
- Stainless steel housing F27: 316L (1.4435)
 - Cover seal: FVMQ (optional: EPDM seal available as spare part)
 - Cover clamp: 316L (1.4435)

Input

Measured variable	<p>Continuous measurement of change in capacitance between probe rod and container wall or ground tube, depending on the level of a liquid.</p> <p>Probe covered => high capacitance Probe not covered => low capacitance</p>
Measuring range	<ul style="list-style-type: none"> ■ Measuring frequency: 500 kHz ■ Span: $\Delta C = 25$ to 4000 pF recommended (2 to 4000 pF possible) ■ Final capacitance: $C_E = \text{max. } 4000 \text{ pF}$ ■ Adjustable initial capacitance: <ul style="list-style-type: none"> – $C_A = 0$ to 2000 pF (< 6 m probe length) – $C_A = 0$ to 4000 pF (> 6 m probe length)
Measuring condition	<ul style="list-style-type: none"> ■ Measuring range L1 possible from the tip of the probe to the process connection. ■ Particularly suited for small containers. <p>Note! When installing in a nozzle, use inactive length (L3).</p> <p>The 0 %, 100 % calibration can be inverted.</p>



L00-FMI5xxxx-15-05-xx-xx-002

Output

Output signal	<p>FEI50H (4 to 20mA/HART Version 5.0)</p> <ul style="list-style-type: none"> ■ 3.8 to 20.5 mA with HART protocol <p>FEI57C (PFM)</p> <ul style="list-style-type: none"> ■ The transmitter superimposes current pulses (PFM signal 60 to 2800 Hz) with a pulse width of approx. 100 µs and a current strength of approx. 8 mA on the supply current (approx. 8 mA).
Signal on alarm	<p>FEI50H</p> <p>Fault diagnosis can be called up as follows:</p> <ul style="list-style-type: none"> ■ Via the local display: <ul style="list-style-type: none"> – Red LED ■ Via the local display showing: <ul style="list-style-type: none"> – Error symbol – Plain text display ■ Via the current output: 22 mA (as per NE43) ■ Via the digital interface (HART status error message) <p>FEI57C</p> <p>Fault diagnosis can be called up as follows:</p> <ul style="list-style-type: none"> ■ Via the local display: <ul style="list-style-type: none"> – Red LED ■ Local display at switching unit
Linearization	<p>FEI50H</p> <p>The Liquicap M linearization function enables conversion of the measured value into any desired length or volume units. Linearization tables for volume calculation of horizontal cylindrical tanks and spherical tanks are pre-programmed. Any other tables with up to 32 value pairs can be input manually or semi-automatically.</p> <p>FEI57C</p> <p>With FEI57C, linearization takes place in the switching units.</p>

Power supply

Electrical connection

Connection compartment


Six housings with the following protection classes are available:

Housing	Standard	EEx ia	EEx d	Gas-tight process seal
Polyester housing F16	X	X	–	–
Stainless steel housing F15	X	X	–	–
Aluminum housing F17	X	X	–	–
Aluminum housing F13	X	X	X	X
Stainless steel housing F27	X	X	X	X
Aluminum housing T13 (with separate connection compartment)	X	X	X	X

Connector

For the version with a connector M12, the housing does not have to be opened for connecting the signal line.


PIN assignment for M12 connector

 L00-FTI5xxxx-04-00-xx-xx-015	PIN	2-wire-electronic insert: FEI50H, FEI57C
	1	+
	2	not used
	3	–
	4	ground

Terminal assignment

2-wire, 4 to 20 mA with HART


The twin-core connecting cable is connected to the screw terminals (conductor cross-section 0.5 to 2.5 mm) in the connection compartment at the electronic insert. If the superimposed communication signal (HART) is used, a shielded cable must be used and the shielding connected at the sensor and power supply. Protective circuits against reverse polarity, HF-influences and overvoltage peaks are integrated (see TI241F "EMC test procedures").



2-wire, PFM

The twin-core, shielded connecting cable with a cable resistance of max. $25\ \Omega$ per core is connected to the screw terminals (conductor cross-section 0.5 to 2.5 mm) in the connection compartment. The shielding must be connected at the sensor and power supply.

Protective circuits against reverse polarity, HF-influences and overvoltage peaks are integrated (see TI241F "EMC test procedures").

**Supply voltage**

All of the following voltages are terminal voltages directly at the device:

FEI50H:

- 12.0 to 36 VDC (in the non-hazardous area)
- 12.0 to 30 VDC (in hazardous areas EEx ia)
- 14.4 to 30 VDC (in hazardous areas EEx d)

FEI57C:

14.8 VDC from associated supply unit.



Note!

Both electronic inserts have integrated reverse polarity protection.

Cable entry

- Cable gland: M20x1.5 (for EEx d only cable entry)
Two cable glands are included in scope of delivery.
- Cable entry: G $\frac{1}{2}$ or $\frac{1}{2}$ NPT

Power consumption**FEI50H**


Min. 40 mW, max. 800 mW

FEI57C

Max. 250 mW

Current consumption**FEI50H (4 to 20 mA/HART)**

- Current consumption: 3.8 to 22 mA
- HART multidrop operation: 4 mA
- Residual ripple HART: 47 to 125 Hz: $U_{ss} = 200\text{ mV}$ (with $500\ \Omega$)
- Noise HART (FEI50H): 500 Hz to 10 kHz: $U_{eff} < 2.2\text{ mV}$ (with $500\ \Omega$)


FEI57C

Frequency: 60 to 2800 Hz

Performance characteristics

Reference operating conditions	<div><div>■ Room temperature: +20 °C ±5 °C</div><div>■ Span: ΔC = 25 to 4000 pF recommended (2 to 4000 pF possible)</div></div>
Maximum measured error	<div><div>■ Non-repeatability (reproducibility) as per DIN 61298-2: max. ±0.1 %</div><div>■ Non-linearity for limit point setting (linearity) as per DIN 61298-2: max. ±0.5 %</div></div>
Influence of ambient temperature	<div><div>Electronic insert</div><div>< 0.06 % / 10 K related to the full scale value</div><div>Separate housing</div><div>Change in capacitance of connecting cable 0.015 pF/m per K</div></div>
Switch-on behavior	<div><div>FEI50H</div><div>14 s (stable measured value after switch-on procedure). start-up in safe state (22mA).</div><div>FEI57C</div><div>1.5 s (stable measured value after switch-on procedure). Start-up in safe state (22mA).</div></div>

Measured value reaction time	<div><div>FEI50H</div><div>$t_1 \leq 0.3\text{ s}$</div><div>$t_1 \leq 0.5\text{ s}$ for operating mode SIL</div><div>FEI57C</div><div>$t_1 = 0.3\text{ s}$</div><div>Note!</div><div>Observe integration time of switching unit</div></div>
------------------------------	---





τ = Integration time
 t_1 = Dead time

Integration time	<div><div>FEI50H</div><div>$\tau = 1\text{ s}$ (factory setting) 0 to 60 s can be set.</div><div>The integration time affects the speed at which the display and the current output react to changes in the level.</div></div>
------------------	---

Accuracy of factory calibration		Probe length < 2 m	Probe length > 2 m
	Empty calibration (0 %)	≤ 5 mm	Approx. 2 %
	Full calibration (100 %)	≤ 5 mm	Approx. 2 %

Medium conductivity ≥ 100 μS/cm
Minimum distance to container wall = 250 mm

-  **Note!**
In an installed state, recalibration is only necessary if:
- The 0 % or the 100 % value have to be adjusted specifically for the customer.
 - The liquid is not conductive.
 - The distance from probe to tank wall is < 250 mm.



Resolution**FEI50H**

Analog in % (4 to 20 mA)

- FMI51, FMI52: 11 bit/2048 steps, 8 μ A
- The resolution of the electronics can be directly converted to units of length of the probe FMI51 or FMI52.
e.g. active probe rod 1000 mm
Resolution = 1000 mm/2048 = 0.48 mm

FEI57C


- Zero frequency f_0 60 Hz:
Sensitivity of the electronic insert = 0.685 Hz/pF
Entry in switching unit FMC671 under V3H5 and V3H6 or V7H5 and V7H6

Human interface

Electronic inserts

FEI50H


- Green LED (ⓘ operational status)
- Red LED (⚡ fault message)
- Key (-)
- Key (+)
- Mode switch
 - 1 : Operation
 - 2 : Empty calibration
 - 3 : Full calibration
 - 4 : Measuring modes (buildup)
 - 5 : Measuring range
 - 6 : Self-test
 - 7 : Reset (factory settings)
 - 8 : Upload sensor EEPROM
- 4 to 20 mA current pick-off, e.g. for full/empty calibration with multimeter.
- Display connection



L00-FMI5xxxx-07-05-xx-xx-000

FEI57C


- Green LED (ⓘ operational status)
- Red LED (⚡ fault message)
- DIP switch, buildup (YES/NO)
- DIP switch, probe length (probe length >6 m/≤6 m)



L00-FMI5xxxx-07-05-xx-xx-002

Local operation with display


The optional display can be used to configure via 3 keys directly at the device. All device functions can be set via menu operation. The menu consists of function groups and functions. Application parameters can be read or set in the functions.



L00-FMI5xxxx-07-05-xx-xx-en-002

Graphic display with operating keys: can be rotated 360°


The menu guidance with integrated help texts ensures quick and safe commissioning. For accessing the display, the cover of the electronics compartment can also be opened in hazardous areas (Ex ia).



L00-FMIxxxxx-07-00-00-es-002

Remote operation with handheld terminal

The handheld terminals FieldXpert SFX100 or Field Communicator DXR375/475 can be used to set all device functions via menu operation.



L00-FMI5xxxxx-07-00-00-xx-007


Remote operation via FieldCare Device Setup

FieldCare is a graphic operating program and is used to support commissioning, data backup, signal analysis and documentation of the devices. The following operating systems are supported: Windows 2000, Windows XP, Windows Vista and Windows 7.

FieldCare supports the following functions:

- Configuration of transmitters in online operation
- Tank linearization
- Loading and saving device data (upload/download)
- Documentation of the measuring point

Menu guided commissioning



Connection options






- HART with Commubox FXA195



Note!

For the latest version of FieldCare see: www.endress.com → Select your country → Search for: FieldCare.

Certificates and approvals

CE mark	The devices are designed to meet state-of-the-art safety requirements, have been tested and left the factory in a condition in which they are safe to operate. The devices comply with the applicable standards and regulations that are listed in the EC Declaration of Conformity and thus meet the legal requirements of the EC Directives. Endress+Hauser confirms the conformity of the device by affixing to it the CE mark.
Ex approval	See "Ordering information" from →  33.
Other standards and guidelines	<p>EN 60529 Degrees of protection by housing (IP code)</p> <p>EN 61010 Protection measures for electrical equipment for measurement, control, regulation and laboratory procedures</p> <p>EN 61326 Interference emission (Class B equipment), interference immunity (Annex A - Industrial).</p> <p>NAMUR Association for Standards for Control and Regulation in the Chemical Industry</p> <p>IEC 61508 Functional safety</p>
Additional approvals	<ul style="list-style-type: none"> ■ See also "Ordering information: approval" →  33 ff. ■ TSE Certificate of Suitability (FMI51) The following applies to wetted device components: <ul style="list-style-type: none"> – They do not contain any materials derived from animals. – No additives or operating materials derived from animals are used in production or processing. <p> Note! The wetted device components are listed in the "Mechanical construction" (→  15 ff) and "Ordering information" (→  33 ff) sections.</p> ■ AD2000 The wetted material (316L) corresponds to AD2000 – W0/W2

Ordering information



Note!

In this list, versions which are mutually exclusive are not marked.

Liquicap M FMI51

10	Approval:
	A Non-hazardous area B Non-hazardous area, WHG (German Water Resources Act) C ATEX II 1/2 GD EEx ia IIC T6 D ATEX II 1/2 GD EEx ia IIC T6, WHG (German Water Resources Act) E ATEX II 1/2 GD EEx ia IIB T6 F ATEX II 1/2 GD EEx ia IIB T6, WHG (German Water Resources Act) G ATEX II 1/2 G EEx d (ia) IIB T6, WHG (German Water Resources Act) H ATEX II 1/2 GD EEx ia IIC T6, XA, observe safety instructions (electrostatic charge)! J ATEX II 1/2 GD EEx ia IIC T6, WHG (German Water Resources Act) XA, observe safety instructions (electrostatic charge)! K ATEX II 1/2 G EEx ia IIC T6, WHG (German Water Resources Act) XA, observe safety instructions (electrostatic charge)! L ATEX II 1/2 G EEx de (ia) IIC T6, WHG (German Water Resources Act) XA, observe safety instructions (electrostatic charge)! M ATEX II 3 GD EEx nA II T6, WHG (German Water Resources Act) XA, observe safety instructions (electrostatic charge)! N CSA General Purpose, C US CSA P CSA/FM IS Cl. I, II, III Div. 1+2 Gr. A-G R CSA/FM XP Cl. I, II, III Div. 1+2 Gr. A-G S TIIS Ex ia IIC T3 T TIIS Ex d IIC T3 1 NEPSI Ex ia IIC T6 2 NEPSI Ex d(ia) IIC T6 4 NEPSI Ex nA IIC T6 5 IECEx Ga/Gb Ex ia IIC T6; Ex iaD 20/Ex tD A21 6 IECEx Ga/Gb Ex ia IIC T6 Y Special version, to be specified
20	Inactive length (L3):
	Price per 100 mm/1 inch L3: 100 to 2000 mm/4 to 80 inch for 316L L3: 150 to 1000 mm/6 to 40 inch for PTFE fully insulated Protection against condensate + bypassing container nozzles 1 Not selected 2 mm L3, 316L 3 mm L3, 316L + PTFE fully insulated 5 inch L3, 316L 6 inch L3, 316L + PTFE fully insulated 9 Special version, to be specified
30	Active probe length (L1); insulation:
	Price per 100 mm/1 inch L1: 100 to 4000 mm/4 to 160 inch for Ø10 mm, Ø16 mm L1: 150 to 3000 mm/6 to 120 inch for Ø22 mm (fully insulated) A mm L1, 10 mm, 316L; PTFE B mm L1, 16 mm, 316L; PTFE C mm L1, 22 mm, 316L; PTFE D mm L1, 16 mm, 316L; PFA E mm L1, 10 mm, 316L; PTFE + ground tube F mm L1, 16 mm, 316L; PTFE + ground tube G mm L1, 16 mm, 316L; PFA + ground tube H inch L1, 0.4 inch, 316L; PTFE K inch L1, 0.6 inch, 316L; PTFE M inch L1, 0.9 inch, 316L; PTFE N inch L1, 0.6 inch, 316L; PFA P inch L1, 0.4 inch, 316L; PTFE + ground tube R inch L1, 0.6 inch, 316L; PTFE + ground tube S inch L1, 0.6 inch, 316L; PFA + ground tube Y Special version, to be specified

50				Process Connection:	Ø Inactive length (mm)	
				Threaded connection		
		GCJ	G ½,	316L, 25 bar	Thread ISO228	22
		GDJ	G ¾,	316L, 25 bar	Thread ISO228	22
		GEJ	G 1,	316L, 25 bar	Thread ISO228	22
		GGJ	G 1½,	316L, 100 bar	Thread ISO228	43
		RCJ	NPT ½,	316L, 25 bar	Thread ANSI	22
		RDJ	NPT ¾,	316L, 25 bar	Thread ANSI	22
		REJ	NPT 1,	316L, 25 bar	Thread ANSI	22
		RGJ	NPT 1½,	316L, 100 bar	Thread ANSI	43
			Hygiene connection			
		GQJ	G ¾ ,	316L, 25 bar, EHEDG	Thread ISO228	–
			Accessories installation, weld-in adapter			
		GWJ	G 1	316L, 25 bar, EHEDG	Thread ISO228	–
			Accessories installation, weld-in adapter			
		MRJ	DN50 PN40,	316L	DIN11851	22/43***
		UPJ	Adapter 44 mm	316L, 16 bar		–
			Tri-Clamp connection			
		TCJ	DN25 (1"), EHEDG	316L,	Tri-Clamp ISO2852	22
		TJJ	DN38 (1½"), EHEDG	316L,	Tri-Clamp ISO2852	22
		TJK	DN38 (1½"), EHEDG	PTFE >316L, 3A	Tri-Clamp ISO2852	22
		TDJ	DN40-51 (2"),	316L,	Tri-Clamp ISO2852	43
		TDK	DN40-51 (2"), EHEDG	PTFE >316L, 3A,	Tri-Clamp ISO2852	–
		TNJ	DN38 (1½"),	316L, 3A, EHEDG	Tri-Clamp ISO2852	–
			Tri-Clamp removable			
			EN flanges			
		B0J	DN25 PN25/40 A,	316L	Flange EN1092-1 (DIN2527 B)	22
		B1J	DN32 PN25/40 A,	316L	Flange EN1092-1 (DIN2527 B)	22
		B2J	DN40 PN25/40 A,	316L	Flange EN1092-1 (DIN2527 B)	22
		B3J	DN50 PN25/40 A,	316L	Flange EN1092-1 (DIN2527 B)	22/43***
		CRJ	DN50 PN25/40 B1,	316L	Flange EN1092-1 (DIN2527 C)	43
		DRJ	DN50 PN40 C,	316L	Flange EN1092-1 (DIN2512 F)	43
		ERJ	DN50 PN40 D,	316L	Flange EN1092-1 (DIN2512 N)	43
		BSJ	DN80 PN10/16 A,	316L	Flange EN1092-1 (DIN2527 B)	43
		CGJ	DN80 PN10/16 B1,	316L	Flange EN1092-1 (DIN2527 C)	43
		DGJ	DN80 PN16 C,	316L	Flange EN1092-1 (DIN2512 F)	43
		EGJ	DN80 PN16 D,	316L	Flange EN1092-1 (DIN2512 N)	43
		BTJ	DN100 PN10/16 A,	316L	Flange EN1092-1 (DIN2527 B)	43
		CHJ	DN100 PN10/16 B1,	316L	Flange EN1092-1 (DIN2527 C)	43
			PTFE clad			
		B0K	DN25 PN25/40,	PTFE >316L	Flange EN1092-1 (DIN2527)	–
		B1K	DN32 PN25/40,	PTFE >316L	Flange EN1092-1 (DIN2527)	–
		B2K	DN40 PN25/40,	PTFE >316L	Flange EN1092-1 (DIN2527)	–
		B3K	DN50 PN25/40,	PTFE >316L	Flange EN1092-1 (DIN2527)	–
		BSK	DN80 PN10/16,	PTFE >316L	Flange EN1092-1 (DIN2527)	–
		BTK	DN100 PN10/16,	PTFE >316L	Flange EN1092-1 (DIN2527)	–
			ANSI flanges			
		ACJ	1" 150 lbs RF,	316/316L	Flange ANSI B16.5	22
		ANJ	1" 300 lbs RF,	316/316L	Flange ANSI B16.5	22
		AEJ	1½" 150 lbs RF,	316/316L	Flange ANSI B16.5	22
		AQJ	1½" 300 lbs RF,	316/316L	Flange ANSI B16.5	22

50					Process Connection:				Ø Inactive length (mm)	
					AFJ	2" 150 lbs RF,	316/316L	Flange ANSI B16.5	22/43***	
					ARJ	2" 300 lbs RF,	316/316L	Flange ANSI B16.5	22/43***	
					AGJ	3" 150 lbs RF,	316/316L	Flange ANSI B16.5	43	
					ASJ	3" 300 lbs RF,	316/316L	Flange ANSI B16.5	43	
					AHJ	4" 150 lbs RF,	316/316L	Flange ANSI B16.5	43	
					ATJ	4" 300 lbs RF,	316/316L	Flange ANSI B16.5	43	
					AJJ	6" 150 lbs RF,	316/316L	Flange ANSI B16.5	43	
					AUJ	6" 300 lbs RF,	316/316L	Flange ANSI B16.5	43	
					PTFE clad					
					ACK	1" 150 lbs,	PTFE >316/316L	Flange ANSI B16.5	—	
					ANK	1" 300 lbs,	PTFE >316/316L	Flange ANSI B16.5	—	
					AEK	1½" 150 lbs,	PTFE >316/316L	Flange ANSI B16.5	—	
					AQK	1½" 300 lbs,	PTFE >316/316L	Flange ANSI B16.5	—	
					AFK	2" 150 lbs,	PTFE >316/316L	Flange ANSI B16.5	—	
					ARK	2" 300 lbs,	PTFE >316/316L	Flange ANSI B16.5	—	
					AGK	3" 150 lbs,	PTFE >316/316L	Flange ANSI B16.5	—	
					AHK	4" 150 lbs,	PTFE >316/316L	Flange ANSI B16.5	—	
					JIS flanges					
					KCJ	10K 25 RF,	316L	Flange JIS B2220	22	
					KEJ	10K 40 RF,	316L	Flange JIS B2220	22	
					KFJ	10K 50 RF,	316L	Flange JIS B2220	22/43***	
					KGJ	10K 80 RF,	316L	Flange JIS B2220	22/43***	
					KHJ	10K 100 RF,	316L	Flange JIS B2220	22/43***	
					KRJ	20K 50 RF,	316L	Flange JIS B2220	43	
					PTFE clad					
					KCK	10K 25 RF,	PTFE >316L	Flange JIS B2220	—	
					KEK	10K 40 RF,	PTFE >316L	Flange JIS B2220	—	
					KFK	10K 50 RF,	PTFE >316L	Flange JIS B2220	—	
					KGK	10K 80 RF,	PTFE >316L	Flange JIS B2220	—	
					KHK	10K 100 RF,	PTFE >316L	Flange JIS B2220	—	
					YY9	Special version, to be specified				
60					Electronics; Output:					
					A	FEI50H; 4 to 20 mA HART + display				
					B	FEI50H; 4 to 20 mA HART				
					C	FEI57C; PFM				
					V	W/o;	prepared for FEI5x + display,	cover high, transparent		
					W	W/o;	prepared for FEI5x,	cover flat		
					Y	Special version, to be specified				
70					Housing:					
					1	F15 316L		IP66, NEMA4X		
					2	F16 polyester		IP66, NEMA4X		
					3	F17 aluminum		IP66, NEMA4X		
					4	F13 aluminum		IP66, NEMA4X		
						+ gas-tight probe seal				
					5	T13 Alu		IP66, NEMA4X		
						+ gas-tight probe seal				
						+ separate connection compartment				
					6	F27 316L		IP68, NEMA6P		
						+ gas-tight probe seal				
					9	Special version, to be specified				
80					Cable Entry:					
					A	Gland M20 (EEx d > thread M20)				
					B	Thread G ½				
					C	Thread NPT ½				
					D	Thread NPT ¾				
					E	Plug M12				
					Y	Special version, to be specified				
90					Type of Probe:					
					L4: 300 to 6000 mm/12 to 240 inch					
					1	Compact				
					2	2000 mm L4 cable	> separate housing			
					3mm L4 cable	> separate housing			
					4	80 inch L4 cable	> separate housing			
					5inch L4 cable	> separate housing			
					9	Special version, to be specified				

Liquicap M FMI52

10	Approval:				
	A	Non-hazardous area			
	B	Non-hazardous area,			WHG (German Water Resources Act)
	E	ATEX II 1/2 GD	EEx ia IIB T6		
	F	ATEX II 1/2 GD	EEx ia IIB T6,	WHG (German Water Resources Act)	
	G	ATEX II 1/2 G	EEx d (ia) IIB T6,	WHG (German Water Resources Act)	
	H	ATEX II 1/2 GD	EEx ia IIC T6,		
		XA, observe safety instructions (electrostatic charge)!			
	J	ATEX II 1/2 GD	EEx ia IIC T6,		
		XA, observe safety instructions (electrostatic charge)!			
	K	ATEX II 1/2 G	EEx ia IIC T6,	WHG (German Water Resources Act)	
		XA, observe safety instructions (electrostatic charge)!			
	L	ATEX II 1/2 G	EEx de (ia) IIC T6,	WHG (German Water Resources Act)	
		XA, observe safety instructions (electrostatic charge)!			
	M	ATEX II 3 GD	EEx nA II T6,	WHG (German Water Resources Act)	
		XA, observe safety instructions (electrostatic charge)!			
	N	CSA General Purpose, C US CSA			
	P	CSA/FM IS	Cl. I, II, III	Div. 1+2 Gr. A-G	
	R	CSA/FM XP Cl. I, II, III	Div. 1+2 Gr. A-G		
	S	TIIIS Ex ia IIC T3			
	T	TIIIS Ex d IIC T3			
	1	NEPSI Ex ia IIC T6			
	2	NEPSI Ex d(ia) IIC T6			
	4	NEPSI Ex nA IIC T6			
	5	IECEX Ga/Gb Ex ia IIC T6; Ex iaD 20/Ex tD A21			
	6	IECEX Ga/Gb Ex ia IIC T6			
	Y	Special version, to be specified			

20	Inactive length (L3):				
	Price per 100 mm/1 inch				
	L3: 100 to 2000 mm/4 to 80 inch for 316L				
	L3: 150 to 1000 mm/6 to 40 inch for PFA fully insulated				
	Protection against condensate + bypassing container nozzles				
	1	Not selected			
	2	... mm L3,	316L		
	3	... mm L3,	316L + PFA fully insulated		
	5	... inch L3,	316L		
	6	... inch L3,	316L + PFA fully insulated		
	9	Special version, to be specified			

30	Active probe length (L1); insulation:				
	Price per 1000 mm/10 inch				
	L1: 420 to 10000 mm/17 to 400 inch; fully insulated				
	A	... mm L1,	316; FEP		
	B	... mm L1,	316; PFA		
	C	... inch L1,	316; FEP		
	D	... inch L1,	316; PFA		
	Y	Special version, to be specified			

50	Process Connection:					Ø Inactive length (mm)
	Threaded connection					
	GDJ	G ¾,	316L, 25 bar	Thread ISO228	22	
	GEJ	G 1,	316L, 25 bar	Thread ISO228	22	
	GGJ	G 1½,	316L, 100 bar	Thread ISO228	43	
	RDJ	NPT ¾,	316L, 25 bar	Thread ANSI	22	
	REJ	NPT 1,	316L, 25 bar	Thread ANSI	22	
	RGJ	NPT 1½,	316L, 100 bar	Thread ANSI	43	
	Hygiene connection					
	GWJ	G 1	316L, 25 bar, EHEDG	Thread ISO228	–	
	Accessories installation, weld-in adapter					
	MRJ	DN50 PN40,	316L	DIN11851	43	
	UPJ	Adapter 44 mm	316L, 16 bar, EHEDG	–		
	Tri-Clamp connection					
	TCJ	DN25 (1"), EHEDG	316L,	Tri-Clamp ISO2852	22	
	TJJ	DN38 (1½"), EHEDG	316L,	Tri-Clamp ISO2852	22	
	TJK	DN38 (1½"), EHEDG	PTFE >316L, 3A	Tri-Clamp ISO2852	22	
	TDJ	DN40-51 (2"),	316L,	Tri-Clamp ISO2852	43	

50	Process Connection:				Ø Inactive length (mm)
	TDK	DN40-51 (2"), EHEDG	PTFE >316L, 3A,	Tri-Clamp ISO2852	—
	EN flanges				
	B0J	DN25 PN25/40 A,	316L	Flange EN1092-1 (DIN2527 B)	22
	B1J	DN32 PN25/40 A,	316L	Flange EN1092-1 (DIN2527 B)	22
	B2J	DN40 PN25/40 A,	316L	Flange EN1092-1 (DIN2527 B)	22
	B3J	DN50 PN25/40 A,	316L	Flange EN1092-1 (DIN2527 B)	43
	CRJ	DN50 PN25/40 B1,	316L	Flange EN1092-1 (DIN2527 C)	43
	DRJ	DN50 PN40 C,	316L	Flange EN1092-1 (DIN2512 F)	43
	ERJ	DN50 PN40 D,	316L	Flange EN1092-1 (DIN2512 N)	43
	BSJ	DN80 PN10/16 A,	316L	Flange EN1092-1 (DIN2527 B)	43
	CGJ	DN80 PN10/16 B1,	316L	Flange EN1092-1 (DIN2527 C)	43
	DGJ	DN80 PN16 C,	316L	Flange EN1092-1 (DIN2512 F)	43
	EGJ	DN80 PN16 D,	316L	Flange EN1092-1 (DIN2512 N)	43
	BTJ	DN100 PN10/16 A,	316L	Flange EN1092-1 (DIN2527 B)	43
	CHJ	DN100 PN10/16 B1,	316L	Flange EN1092-1 (DIN2527 C)	43
	PTFE clad				
	B0K	DN25 PN25/40,	PTFE >316L	Flange EN1092-1 (DIN2527)	—
	B1K	DN32 PN25/40,	PTFE >316L	Flange EN1092-1 (DIN2527)	—
	B2K	DN40 PN25/40,	PTFE >316L	Flange EN1092-1 (DIN2527)	—
	B3K	DN50 PN25/40,	PTFE >316L	Flange EN1092-1 (DIN2527)	—
	BSK	DN80 PN10/16,	PTFE >316L	Flange EN1092-1 (DIN2527)	—
	BTK	DN100 PN10/16,	PTFE >316L	Flange EN1092-1 (DIN2527)	—
	ANSI flanges				
	ACJ	1" 150 lbs RF,	316/316L	Flange ANSI B16.5	22
	ANJ	1" 300 lbs RF,	316/316L	Flange ANSI B16.5	22
	AEJ	1½" 150 lbs RF,	316/316L	Flange ANSI B16.5	22
	AQJ	1½" 300 lbs RF,	316/316L	Flange ANSI B16.5	43
	AFJ	2" 150 lbs RF,	316/316L	Flange ANSI B16.5	43
	ARJ	2" 300 lbs RF,	316/316L	Flange ANSI B16.5	43
	AGJ	3" 150 lbs RF,	316/316L	Flange ANSI B16.5	43
	ASJ	3" 300 lbs RF,	316/316L	Flange ANSI B16.5	43
	AHJ	4" 150 lbs RF,	316/316L	Flange ANSI B16.5	43
	ATJ	4" 300 lbs RF,	316/316L	Flange ANSI B16.5	43
	AJJ	6" 150 lbs RF,	316/316L	Flange ANSI B16.5	43
	AUJ	6" 300 lbs RF,	316/316L	Flange ANSI B16.5	43
	PTFE clad				
	ACK	1" 150 lbs,	PTFE >316/316L	Flange ANSI B16.5	—
	ANK	1" 300 lbs,	PTFE >316/316L	Flange ANSI B16.5	—
	AEK	1½" 150 lbs,	PTFE >316/316L	Flange ANSI B16.5	—
	AQK	1½" 300 lbs,	PTFE >316/316L	Flange ANSI B16.5	—
	AFK	2" 150 lbs,	PTFE >316/316L	Flange ANSI B16.5	—
	ARK	2" 300 lbs,	PTFE >316/316L	Flange ANSI B16.5	—
	AGK	3" 150 lbs,	PTFE >316/316L	Flange ANSI B16.5	—
	AHK	4" 150 lbs,	PTFE >316/316L	Flange ANSI B16.5	—
	JIS flanges				
	KCJ	10K 25 RF,	316L	Flange JIS B2220	22
	KEJ	10K 40 RF,	316L	Flange JIS B2220	22
	KFJ	10K 50 RF,	316L	Flange JIS B2220	43
	KGJ	10K 80 RF,	316L	Flange JIS B2220	43
	KHJ	10K 100 RF,	316L	Flange JIS B2220	43
	KRJ	20K 50 RF,	316L	Flange JIS B2220	43
	PTFE clad				

Endress+Hauser 39

Accessories

Protective cover

For F13, F17 and F27 housing (without display)
Order number: 71040497

For F16 housing
Order number: 71127760

Shortening kit for FMI52

Once the rope is shortened, the device loses its hygiene approval: EHEDG, 3A.
Order number: 942901-0001

Commubox FXA191, FXA195 HART


For intrinsically safe HART communication with FieldCare via a USB port.

Overvoltage protection HAW56x

Surge arrester for limiting overvoltage in signal lines and components.

Overvoltage protection (installation on housing M20x1.5)

- HAW569-A11A (non-hazardous)
- HAW569-B11A (hazardous area)



L00-FMI5xxxx-03-05-xx-xx-009

Overvoltage protection (installation in cabinet)

- HAW562Z (hazardous area)


Weld-in adapter

All the weld-in adapters available are described in the document TI426F.
www.endress.com => Country => Download => Advanced => Documentation code => TI426F.

Spare Parts

An overview of the spare parts for your device is available in the internet at www.endress.com.
To obtain information on the spare parts, proceed as follows:

1. Go to "www.endress.com" and select your country.
2. Click "Instruments".



3. Enter the product name into the "product name" field.

Endress+Hauser product search

Via product name
Enter the product name

4. Select the device.

5. Click the "Accessories/Spare parts" tab.

General information

Technical information

Documents/Software

Service

Accessories/Spare parts

► Accessories

▼ All Spare parts

► Housing/housing accessories

► Sealing

► Cover


► Terminal module

► HF module

► Electronic

► Power supply

► Antenna module



Advice

Here you'll find a list of all available accessories and spare parts. To only view accessories and spare parts specific to your product(s), please contact us and ask about our Life Cycle Management Service.

◀

1 / 2

▶

6. Select the required spare parts (You may also use the overview drawing on the right side of the screen.)
When ordering spare parts, always quote the serial number indicated on the nameplate. As far as necessary, the spare parts also include replacement instructions.

Documentation



Note!
The following documentation is available on the product pages at www.endress.com

Technical Information	<ul style="list-style-type: none">Fieldgate FXA320, FXA520 TI00369F/00/en
Operating Instructions	<ul style="list-style-type: none">Liquicap M FMI51, FMI52 (PFM) BA00297F/00/enLiquicap M FMI51, FMI52 (HART) BA00298F/00/en
Certificates	<div><div>ATEX safety instructions</div><div><ul style="list-style-type: none">Liquicap M FMI51, FMI52 ATEX II 1/2 G EEx ia IIC/IIB T3 to T6, II 1/2 D IP65 T 85 °C XA00327F/00/a3Liquicap M FMI51, FMI52 ATEX II 1/2 G EEx d [ia] IIC/IIB T3 to T6 XA00328F/00/a3Liquicap M FMI51, FMI52 Ga/Gb Ex ia IIC T6-T3; Ex ia D 20 / Ex tD A21 IP65 T90°C XA00423F/00/a3</div></div> <div><div>NEPSI safety instructions</div><div><ul style="list-style-type: none">Liquicap M FMI51, FMI52 Ex ia IIC/IIB T3 to T6 XA00417F/00/a3Liquicap M FMI51, FMI52 EEx d [ia] IIC/IIB T3 to T6 XA00418F/00/a3Liquicap M FMI51, FMI52 Ex nA II T3-T6, Ex nC IIC T3-T6 XA00430F/00/a3</div></div> <div><div>Overfill protection DIBt (WHG)</div><div><ul style="list-style-type: none">Liquicap M FMI51, FMI52</div></div>

ZE00265F/00/de

Functional safety (SIL2)

- Liquicap M FMI51, FMI52
SD00198F/00/en

Control Drawings (CSA and FM)

- Liquicap M FMI51, FMI52
FM
ZD00220F/00/en
- Liquicap M FMI51, FMI52
CSA
ZD00221F/00/en

CRN registration

- CRN 0F1988.75

Patents

This product is protected by at least one of the patents listed below.
Further patents are under development.

- DE 103 22 279,
WO 2004 102 133,
US 2005 003 9528
- DE 203 13 695,
WO 2005 025 015

Instruments International

Endress+Hauser
Instruments International AG
Kaegenstrasse 2
4153 Reinach
Switzerland

Tel. +41 61 715 81 00
Fax +41 61 715 25 00
www.endress.com
info@ii.endress.com

Endress+Hauser 
People for Process Automation

